

Thrust and tension screw (3x120°)
for tilt adjustment
with hex key wrench size 1.5mm
50HD-15 ①

clamp screws
for accessory optics (3x120°)
using hex-key size 1.5mm
50HD-15 ①

Fiber receptacle
type FC-SMA-905
High Power Connector (5° polish)

Thrust screw M3 max.torque 50Ncm

Tension screw M2 max.torque 40Ncm

clamp screws for locking optics position (2x120°)
using hex-key size 1.5mm
50HD-15 ①


adjustment of focus setting
using eccentric-key 55EX-5 ②

! Don't touch any other screws !

Tools for assembly and adjustment

hex-key
size 1.5mm
50HD-15 ①

eccentric-key
55EX-5 ②



Allgemein- toleranz ISO 2768 - f		Maßstab: 2:1	60FC-SMA-T-23-f'30-40	
Bearb.	30.11.2016	Datum	Name	Fiber collimator f'30-40mm
Gepr.				
Norm				
Schäfter&Kirchhoff OPTO-SENSORIK UND MESSTECHNIK OPTIK-ENTWICKLUNG/ELEKTRONIK/SENSORTECHNIK/SOFTWARE				Fiber receptacle type FC-SMA-905 High Power Connector (5° polish)
9803-1223-5500				Blatt A3
Zust. Änderungen Datum Name Datei: 980312235500.idw				Blatt: 2
Modell: 980312235500.iam				