

clamp screws
for locking of lens attachments (3x120°)
screws not included

Fiber receptacle
type FC-APC
(wide key)

clamp screws
for locking optics position (2x120°)
using screw-driver size 1.2mm
9D-12 ①

adjustment of focus setting
using eccentric-key 60EX-4 ②

! Pin screw for additional locking of the fiber ferrule:
- before pulling the FC-APC-connector:
unlock the pin screw.
-before inserting the FC-APC-connector:
make sure the ferrule is not blocked
by the pin screw!
(using screw-driver size 1.2mm 9D-12 ①)

adjustment of focus setting
using eccentric-key 60EX-4 ②

clamp screws for locking optics position (2x120°)
using screw-driver size 1.2mm
9D-12 ①

Fiber receptacle
type FCP8
(wide key)

for fiber connector type FCP8

for fiber connector type FC-APC

! Don't touch any other screws !



Tools for assembly and adjustment

screw driver
size 1.2mm
9D-12

eccentric-key
60EX-4

①

②



Allgemein- toleranz ISO 2768 - f		Maßstab:	
Datum 14.06.2016		Name A. Trapp	
60FC-4-XX-DI			
Fiber collimator f' 1.5 to 12mm			
60FC-4-XX-DI for fiber connector type FCP8			
Schäfter&Kirchhoff OPTO-SENSORIK UND MESSTECHNIK OPTIK-ENTWICKLUNG/ELEKTRONIK/SENSORTECHNIK/OPTIKFIBRE			Blatt A3
Datei: 970920520561.idw			Blatt 2
Zust.		Änderungen	
Datum		Name	
Model: 970920520561.iam			