

Line Scan Camera SK5150VJR-L

CCD

monochrome



Digital camera with very high sensitivity
for high line frequencies



■ Sensor Characteristics

Sensor type:	CCD, Monochrome
Pixel number:	5148
Pixel size:	7 x 7 μm^2
Active sensor length:	36 mm
Max. pixel frequency:	40 MHz
Max. line frequency:	7.52 kHz
Min. integration time:	0.01 ms
Max. integration time:	20 ms
Spectral range:	400 - 900 nm
Dynamic range:	1:500 (rms)

■ Mechanical data


Case type:	BG3
Size:	65 mm x 65 mm x 72.4 mm
Mass:	0.3 kg
Lens mount:	M45x0.75
Flange focal length (FFL):	19.5 mm
Seat for bracket:	$\text{Ø}47.5$ mm

■ Functioning Features

Blooming protection:	-
Integration Control:	-
Shading correction:	x
Look-up table:	x
Region of interest (ROI):	x
Thresholding:	-
Temperature sensor:	x
External synchronization:	x
Operating temperature:	+5 ... +45°C

■ Connections

Interface:	GigE Vision
	RJ-45 (8P8C)
Video signals:	monochrome 8/12 Bit digital
Power supply:	+5/+15V DC 3.5
	Hirose 10A, 6-pin, male
External synchronization:	TTL
	Hirose 10A, 12-pin, male



Software



The Schäfter + Kirchhoff GigE Vision™ line scan cameras use the Gigabit Ethernet communication protocol and are 100% compliant with the GigE Vision™ specifications and the Gen<i>i>Cam™ standard. They implement a superset of the Gen<i>i>Cam™ specification which defines the device capabilities. The settings are made in the device feature list of any Gen<i>i>Cam™ compliant software.

The Gen<i>i>Cam™ standard provides a generic programming interface for all kinds of cameras and, no matter what features they implement, the application programming interface (API) always remains the same.

Accessories

CAT6 Network cable

Shielded CAT6 patch cable, halogen-free, both ends with RJ45 connectors for Gigabit Ethernet

CAT6.x **Order Code**

_____ cable length 3 / 5 / 10 m or length according to choice, max. 100 m

Power supply unit PS051515

Input: 100-240 VAC, 0.8 A, 50/60 Hz
IEC 60320 C14 coupler (for IEC C13 power cord)

Output: +5VDC, 2.5 A / +15VDC, 0.5 A / -15VDC, 0.3 A
Cable length: 1 m, with Lumberg connector KV60, female 6-pin

PS051515 **Order Code**

Power cord IEC 60320 C13, 1.5 m, 10 A, 250 VAC

PC150DE **Order Code**

_____ DE = Europe / US = USA, Canada, Japan / UK = United Kingdom

External synchronization cable SK9024...

for line scan cameras with GigE / GigE Vision™ interface.

Shielded cable with Hirose plug HR10A, female 12-pin (camera side), and Phoenix 4-pin connector incl. terminal block.

SK9024.x **Order Code**

_____ cable length 3 / 5 m
Other lengths on request

Power cable SK9015.x

for GigE Vision™, CameraLink and externally supplied USB3 line scan cameras.

Shielded cable with Hirose plug HR10A, female 6-pin (camera side), and Lumberg SV60, male 6-pin connector (power supply unit side).

SK9015.x **Order Code**

_____ cable length 0.2 / 1.5 m

Adapter cable for sync signals CAB-ADSync-BNC-1

BNC/SMA (3x) to line scan camera synchronization cable SK9016/SK9024/SK9026.

Shielded cable, length 0.25 m

Connectors:
1x Phoenix 4-pin connector
3x SMA plug (Line Sync A, Line Sync B, Frame Sync)
3x adapter SMA socket (outside thread) to BNC-plug

CAB-ADSync-BNC-1 **Order Code**

M2 Mounting Bracket SK5105-L

For cameras with lens thread size M45x0.75

SK5105-L with clamping set SK5101#

MC2 Clamping Set SK5101

Clamp SK5101 (set of 4 pcs.)
Allen screw DIN 912-M3x12

M4 Mounting System SK5105-2L

For camera configurations with tube length > 55 mm using extension rings **ZR-L**

FA3 Focus adapter L-Mount (M39x1/26" Leica)

any rotation angle adjustable (V-groove)
attachment thread M45x0.75, male

FA22R-45 **Order Code**
length L: 22 ... 32 mm

FA22RL-45 **Order Code**
length L: 29 ... 38 mm

A3 Lens Adapter F-Mount

for line scan cameras with case type **Axx** or **BGx**.

AOC-F-... **Order Code**

Attachment thread:
45 = M45x0.75
40 = M40x0.75
32 = M32x0.75
C = C-Mount 1"-32-TP

ZR-L Extension rings M45x0.75

attachment threads M45x0.75 male/female

ZR-L.25 **Order Code**

15 = Length 15 mm
25 = Length 25 mm
60 = Length 60 mm
87 = Length 87 mm