13LN40-S500+90CM-635-4-H10-M60-C-6

Micro Line Generator with a fan angle




FEATURES

Laser line with a fan angle, approx. uniform intensity distribution and very thin lines.

- Line length: 150 mm
- Line width: 29 µm
- Wavelength: 635 nm
- Working distance: 491.5 mm

- Micro Line Generator for small laser line widths and high power density in the focal plane



DESCRIPTION

The laser diode beam source type 13LN40-S500+90CM-635-4-H10-M60-C-6 has a fan angle of 15.8° and approx. uniform intensity distribution along the laser line.

More precisely, it is Gaussian clipped by an aperture with an edge intensity of 84 %. Across the laser line the intensity distribution is Gaussian. The line width is constant along 60 % of the central are, outside this area the line width differs up to 30 %.

The laser has integrated electronics type C for control of the laser output power. The output power can be controlled using the modulation input ports (TTL and analog) or manually using the potentiometer.

For this laser type the working distance is fixed. A fine-adjustment of the distance between laser and target is recommended for fine-focusing in order to achieve minimal line width.

TECHNICAL DATA

13LN40-S500+90CM-635-4-H10-M60-C-6

Series		13LN40
Order Code		13LN40-S500+90CM-635-4-H10-M60-C-6
Line profile		Constant Intensity Distribution
Line type		Laser Micro Line
Wavelength		635 +10/-10 nm
Laser output power		4 mW
Laser safety class		3R
Fan angle α		15.8 deg
Focussing range		491.5-491.5 mm
Working distance		491.5 mm
Line length		150 mm
Line width		0.029 mm
Rayleigh range		2.06 mm
Edge intensity		84 %
Diameter laser module		25/28 mm
Module length		125.9 mm
Installation length		647.4 mm
Cable length		1.5 m
Connector type		Lumberg SV50 IEC 61076-2-106
Supply voltage		5 ± 0.2 V
Max. current consumption		0.25 A
Working temperature		0 - 40 °C
Modulation inputs	Analog	TTL
Input resistance	22 kOhm	22 kOhm
Max. modulation frequency	100 kHz	100 kHz
Modulation delay ON/OFF	1/0.5 µs	2/1 µs
Rise / Fall time	3/2 µs	3/2 µs

DOWNLOADS

951210000056.pdf

ACCESSORIES

9D-12	Screwdriver WS 1.2
PS051003E	Power Supply 5 V

RELATED PRODUCTS

LASER MODULES SERIES 13LNM	▪ Micro Line Generator, **small** fan angle ▪ Uniform intensity distribution ▪ Extended depth of focus
LASER MODULES SERIES LNC-13LN	▪ Micro Line, **small** fan angle ▪ Uniform intensity distribution ▪ Thin lines ▪ Low noise
LASER MODULES SERIES 13LR	▪ Micro Line Generator, fan angle ▪ Uniform intensity distribution
LASER MODULES SERIES 5LM+25CM	▪ **Compact** Micro Line, **small** fan angle ▪ Gaussian intensity distribution
LASER MODULES SERIES 5LP+25CM	▪ **Compact** Micro Line, **large** fan angle ▪ Gaussian intensity distribution
LASER MODULES SERIES 5LM	▪ Micro Line, **small** fan angle ▪ Gaussian intensity distribution
LASER MODULES SERIES 5LP	▪ Micro Line, **large** fan angle ▪ Gaussian intensity distribution

This is a printout of the page https://sukhamburg.com/products/details/13LN40-S500_90CM-635-4-H10-M60-C-6 from 3/28/2024

CONTACT

For more information please contact:
Schäfter + Kirchhoff GmbH
Kieler Str. 212
22525 Hamburg
Germany
Tel: +49 40 85 39 97-0
Fax: +49 40 85 39 97-79

info@sukhamburg.de
www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]