13LR12-S000+55CM-635-10-H10-T12-C-6


Laser Micro Line Generator with a fan angle



FEATURES

Laser line with a fan angle and approx. uniform intensity distribution.

- Line length: 409 mm
- Line width: 569 μm
- Wavelength: 635 nm
- Working distance: 2000 mm
- Micro Line Generator for small laser line widths and high power density in the focal plane



DESCRIPTION

The laser diode beam source type 13LR12-S000+55CM-635-10-H10-T12-C-6 has a fan angle of 12° with a constant line width and approx. uniform intensity distribution along the laser line.

The fine-structure is a <u>chain of equidistant dots</u> with a spacing of approx. the line width. The line width is constant along the laser line. Across the laser line the intensity distribution is Gaussian.

The laser has integrated electronics <u>type C</u> for control of the laser output power. The output power can be controlled using the <u>modulation input ports (TTL and analog)</u> or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance.



A fine-adjustment of the distance between laser and target is recommended for fine-focusing.


TECHNICAL DATA

13LR12-S000+55CM-635-10-H10-T12-C-6

Series		13LR
Order Code	13LR12-S000+55CM-635-10-H10-T12-C-6	
Line profile	Constant Intensity Distribution	
Line type	Laser Micro Line	
Wavelength	635 +10/-10 nm	
Laser output power	10 mW	
Laser safety class	3В	
Fan angle α	12 deg	
bcussing range 1300-inf mm		
Working distance	rking distance 2000 mm	
Line length	409 mm	
Line width	0.569 mm	
Rayleigh range	802 mm	
Edge intensity	80 %	
Diameter laser module	25/28 mm	
Module length	75.9 mm	
Installation length	2105.9 mm	
Cable length1.5 m		1.5 m
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 ± 0.2 V	
Max. current consumption	0.25A	
Working temperature	0 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	22 kOhm	22 kOhm
Max. modulation frequency	100 kHz	100 kHz
Modulation delay ON/OFF	1/0.5 µs	2/1 µs
Rise / Fall time	3/2 µs	3/2 µs



DATA SHEET



Dimensions (for a complete dimensional drawing please refer to the downloads section)

DOWNLOADS



I

ACCESSORIES

50HD-15	Hex key WS 1.5
9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile
PS051003E	Power Supply 5 V

RELATED PRODUCTS

LASER MODULES SERIES 13LRM

- Macro Line Generator, fan angle
- Uniform intensity distribution
- Extended depth of focus

LASER MODULES SERIES 13LN

- Micro Line, small fan angle
- Uniform intensity distribution
- Thin lines



DATA SHEET

LASER MODULES SERIES 5LM+25CM	 Compact Micro Line, small fan angle Gaussian intensity distribution
LASER MODULES SERIES 5LP+25CM	 Compact Micro Line, large fan angle Gaussian intensity distribution
LASER MODULES SERIES 5LM	 Micro Line, small fan angle Gaussian intensity distribution
LASER MODULES SERIES 5LP	 Micro Line, large fan angle Gaussian intensity distribution

This is a printout of the page <u>https://sukhamburg.com/products/details/13LR12-S000_55CM-635-10-H10-T12-C-6</u> from 5/3/2024

CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]

