

13LRM12-S000-1.5+55CM-635-6-H10-T15-C-6

Laser Macro Line Generator with a fan angle



FEATURES

Laser line with a fan angle, approx. uniform intensity distributionand extended depth of focus.

Line width: 1220 µm
Wavelength: 635 nm
Working distance: 2000 mm
Depth of focus: 3000 mm

Line length: 409 mm

Macro Line Generator for extended depth of focus



DESCRIPTION

The laser diode beam source type 13LRM12-S000-1.5+55CM-635-6-H10-T15-C-6 has a fan angle of 12° with a constant line width and approx. uniform intensity distribution along the laser line as well an extended depth of focus.

The fine-structure is a <u>chain of equidistant dots</u> with a spacing of approx. 1/2 the line width. The line width is constant along the laser line. Across the laser line the intensity distribution is approx. Gaussian.

The laser has integrated electronics $\underline{type\ C}$ for control of the laser output power. The output power can be controlled using the $\underline{modulation\ input\ ports\ (TTL\ and\ analog)}$ or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance.



A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

13LRM12-S000-1.5+55CM-635-6-H10-T15-C-6

Max. modulation frequency100 kHz100 kHzModulation delay ON/OFF1/0.5 μs2/1 μs	Series 13LRM			
Line type Laser Macro Line Wavelength 635 +10/-10 nm Laser output power 6 mW Laser safety class 3B Fan angle α 12 deg Focussing range 1330-inf mm Working distance 2000 mm Line length 409 mm Line width 1.22 mm Depth of focus 3000 mm Edge intensity 80 % Diameter laser module 25/28 mm Module length 86.8 mm Installation length 2116.8 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.2 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation delay ON/OFF 1/0.5 μs 2/1 μs	Order Code	13LRM12-S000-1.5+55CM-635-6-H10-T15-C-6		
Wavelength 635 +10/-10 nm Laser output power 6 mW Laser safety class 3B Fan angle α 12 deg Focussing range 1330-inf mm Working distance 2000 mm Line length 409 mm Line width 1.22 mm Depth of focus 3000 mm Edge intensity 80 % Diameter laser module 25/28 mm Module length 86.8 mm Installation length 2116.8 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.2 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz Modulation delay ON/OFF 1/0.5 μs 2/1 μs	Line profile	Constant Intensity Distribution		
Laser output power 6 mW Laser safety class 3B Fan angle α 12 deg Focussing range 1330-inf mm Working distance 2000 mm Line length 409 mm Line width 1.22 mm Depth of focus 3000 mm Edge intensity 80 % Diameter laser module 25/28 mm Module length 86.8 mm Installation length 2116.8 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.2 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz Modulation delay ON/OFF 1/0.5 μs 2/1 μs	Line type	Laser Macro Line		
Laser safety class3BFan angle α12 degFocussing range1330-inf mmWorking distance2000 mmLine length409 mmLine width1.22 mmDepth of focus3000 mmEdge intensity80 %Diameter laser module25/28 mmModule length86.8 mmInstallation length2116.8 mmCable length1.5 mConnector typeLumberg SV50 IEC 61076-2-106Supply voltage $5 \pm 0.2 \text{ V}$ Max. current consumption0.25 AWorking temperature $0 - 40 ^{\circ}\text{C}$ Modulation inputsAnalogTTLInput resistance22 kOhm22 kOhmMax. modulation frequency 100kHz 100kHz Modulation delay ON/OFF $1/0.5 \mu\text{s}$ $2/1 \mu\text{s}$	Wavelength	635 +10/-10 nm		
Fan angle α12 degFocussing range1330-inf mmWorking distance2000 mmLine length409 mmLine width1.22 mmDepth of focus3000 mmEdge intensity80 %Diameter laser module25/28 mmModule length86.8 mmInstallation length2116.8 mmCable length1.5 mConnector typeLumberg SV50 IEC 61076-2-106Supply voltage $5 \pm 0.2 \text{ V}$ Max. current consumption0.25 AWorking temperature0 - 40 °CModulation inputsAnalogTTLInput resistance22 kOhm22 kOhmMax. modulation frequency100 kHz100 kHzModulation delay ON/OFF1/0.5 μs2/1 μs	Laser output power	6 mW		
Focussing range 1330-inf mm Working distance 2000 mm Line length 409 mm Line width 1.22 mm Depth of focus 3000 mm Edge intensity 80 % Diameter laser module 25/28 mm Module length 86.8 mm Installation length 2116.8 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.2 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz Modulation delay ON/OFF 1/0.5 μs 2/1 μs	Laser safety class	3B		
Working distance 2000 mm Line length 409 mm Line width 1.22 mm Depth of focus 3000 mm Edge intensity 80 % Diameter laser module 25/28 mm Module length 86.8 mm Installation length 2116.8 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.2 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz Modulation delay ON/OFF 1/0.5 μs 2/1 μs	Fan angle α	12 deg		
Line length 409 mm Line width 1.22 mm Depth of focus 3000 mm Edge intensity 80 % Diameter laser module 25/28 mm Module length 86.8 mm Installation length 2116.8 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.2 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz Modulation delay ON/OFF 1/0.5 μs 2/1 μs	Focussing range	1330-inf mm		
Line width 1.22 mm Depth of focus 3000 mm Edge intensity 80 % Diameter laser module 25/28 mm Module length 86.8 mm Installation length 2116.8 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.2 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz Modulation delay ON/OFF 1/0.5 μs 2/1 μs	Working distance	2000 mm		
Depth of focus $3000 \mathrm{mm}$ Edge intensity 80% Diameter laser module $25/28 \mathrm{mm}$ Module length $86.8 \mathrm{mm}$ Installation length $2116.8 \mathrm{mm}$ Cable length $1.5 \mathrm{m}$ Connector typeLumberg SV50 IEC 61076-2-106Supply voltage $5 \pm 0.2 \mathrm{V}$ Max. current consumption $0.25 \mathrm{A}$ Working temperature $0 - 40 ^{\circ}\mathrm{C}$ Modulation inputsAnalogTTLInput resistance $22 \mathrm{kOhm}$ $22 \mathrm{kOhm}$ Max. modulation frequency $100 \mathrm{kHz}$ $100 \mathrm{kHz}$ Modulation delay ON/OFF $1/0.5 \mu \mathrm{s}$ $2/1 \mu \mathrm{s}$	Line length	409 mm		
Edge intensity80 %Diameter laser module25/28 mmModule length86.8 mmInstallation length2116.8 mmCable length1.5 mConnector typeLumberg SV50 IEC 61076-2-106Supply voltage5 ± 0.2 VMax. current consumption0.25 AWorking temperature0 - 40 °CModulation inputsAnalogTTLInput resistance22 kOhmMax. modulation frequency100 kHzModulation delay ON/OFF1/0.5 μs2/1 μs	Line width	1.22 mm		
Diameter laser module25/28 mmModule length86.8 mmInstallation length2116.8 mmCable length1.5 mConnector typeLumberg SV50 IEC 61076-2-106Supply voltage5 ± 0.2 VMax. current consumption0.25 AWorking temperature0 - 40 °CModulation inputsAnalogTTLInput resistance22 kOhm22 kOhmMax. modulation frequency100 kHz100 kHzModulation delay ON/OFF1/0.5 μs2/1 μs	Depth of focus	3000 mm		
Module length86.8 mmInstallation length2116.8 mmCable length1.5 mConnector typeLumberg SV50 IEC 61076-2-106Supply voltage $5 \pm 0.2 \text{V}$ Max. current consumption0.25 AWorking temperature $0 - 40 ^{\circ}\text{C}$ Modulation inputsAnalogTTLInput resistance 22kOhm 22kOhm Max. modulation frequency 100kHz 100kHz Modulation delay ON/OFF $1/0.5 \mu \text{s}$ $2/1 \mu \text{s}$	Edge intensity	80 %		
Installation length2116.8 mmCable length1.5 mConnector typeLumberg SV50 IEC 61076-2-106Supply voltage5 ± 0.2 VMax. current consumption0.25 AWorking temperature0 - 40 °CModulation inputsAnalogTTLInput resistance22 kOhm22 kOhmMax. modulation frequency100 kHz100 kHzModulation delay ON/OFF1/0.5 μs2/1 μs	Diameter laser module	25/28 mm		
Cable length $1.5 \mathrm{m}$ Connector typeLumberg SV50 IEC 61076-2-106Supply voltage $5 \pm 0.2 \mathrm{V}$ Max. current consumption $0.25 \mathrm{A}$ Working temperature $0 - 40 ^{\circ}\mathrm{C}$ Modulation inputsAnalogTTLInput resistance $22 \mathrm{kOhm}$ $22 \mathrm{kOhm}$ Max. modulation frequency $100 \mathrm{kHz}$ $100 \mathrm{kHz}$ Modulation delay ON/OFF $1/0.5 \mu \mathrm{s}$ $2/1 \mu \mathrm{s}$	Module length	86.8 mm		
	Installation length	2116.8 mm		
	Cable length	1.5 m		
Max. current consumption0.25 AWorking temperature0 - 40 °CModulation inputsAnalogTTLInput resistance22 kOhm22 kOhmMax. modulation frequency100 kHz100 kHzModulation delay ON/OFF1/0.5 μs2/1 μs	Connector type	Lumberg SV50 IEC 61076-2-106		
Working temperature0 - 40 °CModulation inputsAnalogTTLInput resistance22 kOhm22 kOhmMax. modulation frequency100 kHz100 kHzModulation delay ON/OFF1/0.5 μs2/1 μs	Supply voltage	5 ± 0.2 V		
Modulation inputsAnalogTTLInput resistance22 kOhm22 kOhmMax. modulation frequency100 kHz100 kHzModulation delay ON/OFF1/0.5 μs2/1 μs	Max. current consumption	0.25 A		
Input resistance22 kOhmMax. modulation frequency100 kHzModulation delay ON/OFF1/0.5 μs	Working temperature	0 - 40 °C		
Max. modulation frequency100 kHz100 kHzModulation delay ON/OFF1/0.5 μs2/1 μs	Modulation inputs	Analog	TTL	
Modulation delay ON/OFF1/0.5 μs2/1 μs	Input resistance	22 kOhm	22 kOhm	
	Max. modulation frequency	100 kHz	100 kHz	
Rise / Fall time 3/2 μs 3/2 μs	Modulation delay ON/OFF	1/0.5 μs	2/1 μs	
· · · · · · · · · · · · · · · · · · ·	Rise / Fall time		3/2 µs	



DOWNLOADS



ACCESSORIES

50HD-15 Hex key WS 1.5

9D-12 Screwdriver WS 1.2

13MK-25-36-10-F Mounting Console with flat base plate

13MK-25-36-10-M Mounting Console with base plate with dovetail

profile

PS051003E Power Supply 5 V

RELATED PRODUCTS

LASER MODULES SERIES 13LR

- Micro Line Generator, fan angle
- Uniform intensity distribution

LASER MODULES SERIES 13LNM

- Micro Line Generator, small fan angle
- Uniform intensity distributionExtended depth of focus

LASER MODULES
SERIES 5LMM+25CM

- Compact Micro Line, small fan angle
- Gaussian intensity distribution
- Extended depth of focus

LASER MODULES
SERIES 5LPM+25CM

- Compact Macro Line, large fan angle
- Gaussian intensity distribution
- Extended depth of focus

LASER MODULES SERIES 5LMM

- Macro Line, small fan angle
- Gaussian intensity distribution
- Extended depth of focus

LASER MODULES SERIES 5LPM

- Macro Line, large fan angle
- Gaussian intensity distribution
- Extended depth of focus



This is a printout of the page https://sukhamburg.com/products/details/13LRM12-S000-1 5 55CM-635-6-H10-T15-C-6 from 5/5/2024

CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany

Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]