

13LRM12-S000-1.5+55CM-639-14-H18-T12-CS-7

Laser Macro Line Generator with a fan angle



FEATURES

Laser line with a fan angle, approx. uniform intensity distribution and extended depth of focus.

- Line length: 409 mm
- Line width: 1240 μm
- Wavelength: 639 nm
- Working distance: 2000 mm
- Depth of focus: 3000 mm

- Macro Line Generator for extended depth of focus
- With RS232 interface



DESCRIPTION

The laser diode beam source type 13LRM12-S000-1.5+55CM-639-14-H18-T12-CS-7 has a fan angle of 12° with a constant line width and approx. uniform intensity distribution along the laser line as well as an extended depth of focus.

The fine-structure is a [chain of equidistant dots](#) with a spacing of approx. 1/2 the line width. The line width is constant along the laser line. Across the laser line the intensity distribution is approx. Gaussian.

The laser has integrated electronics [type CS](#) for control of the laser output power and serial interface (RS232). The output power can be controlled using the [modulation input ports \(TTL and analog\)](#), or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance.

A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

13LRM12-S000-1.5+55CM-639-14-H18-T12-CS-7

Series	13LRM	
Order Code	13LRM12-S000-1.5+55CM-639-14-H18-T12-CS-7	
Line profile	Constant Intensity Distribution	
Line type	Laser Macro Line	
Wavelength	639 +10/-10 nm	
Laser output power	14 mW	
Laser safety class	3B	
Fan angle α	12 deg	
Focussing range	1330-inf mm	
Working distance	2000 mm	
Line length	409 mm	
Line width	1.24 mm	
Depth of focus	3000 mm	
Edge intensity	80 %	
Diameter laser module	25/28 mm	
Module length	86.8 mm	
Installation length	2116.8 mm	
Cable length	1.5 m	
Connector type	Lumberg SV70 IEC 61076-2-106	
Supply voltage	5 \pm 0.2 V	
Max. current consumption	0.25 A	
Working temperature	0 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	9 kOhm	9 kOhm
Max. modulation frequency	0.001 kHz	250 kHz
Modulation delay ON/OFF	3000/3000 μ s	0.5/0.2 μ s
Rise / Fall time	200000/200000 μ s	0.8/0.4 μ s
Interface	RS232	

DOWNLOADS

[930412000124.pdf](#)

ACCESSORIES

50HD-15	Hex key WS 1.5
9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile
PS051007E	Power Supply 5 V for laser modules with RS232 interface

RELATED PRODUCTS

LASER MODULES SERIES 13LR	<ul style="list-style-type: none">▪ Micro Line Generator, fan angle▪ Uniform intensity distribution
LASER MODULES SERIES 13LNM	<ul style="list-style-type: none">▪ Micro Line Generator, small fan angle▪ Uniform intensity distribution▪ Extended depth of focus
LASER MODULES SERIES 5LMM+25CM	<ul style="list-style-type: none">▪ Compact Micro Line, small fan angle▪ Gaussian intensity distribution▪ Extended depth of focus
LASER MODULES SERIES 5LPM+25CM	<ul style="list-style-type: none">▪ Compact Macro Line, large fan angle▪ Gaussian intensity distribution▪ Extended depth of focus
LASER MODULES SERIES 5LMM	<ul style="list-style-type: none">▪ Macro Line, small fan angle▪ Gaussian intensity distribution▪ Extended depth of focus
LASER MODULES SERIES 5LPM	<ul style="list-style-type: none">▪ Macro Line, large fan angle▪ Gaussian intensity distribution▪ Extended depth of focus

This is a printout of the page https://sukhamburg.com/products/details/13LRM12-S000-1_5_55CM-639-14-H18-T12-CS-7 from 5/8/2024

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)