

13LRM25-M125-1.5+55CM-660-60-M25-T12-P-6

Laser Macro Line Generator with a fan angle



FEATURES

Laser line with a fan angle, approx. uniform intensity distribution and extended depth of focus.

- Line length: 55 mm
- Line width: 79 μm
- Wavelength: 660 nm
- Working distance: 111 mm
- Depth of focus: 20.4 mm

- Macro Line Generator for extended depth of focus



DESCRIPTION

The laser diode beam source type 13LRM25-M125-1.5+55CM-660-60-M25-T12-P-6 has a fan angle of 25° with a constant line width and approx. uniform intensity distribution along the laser line as well as an extended depth of focus.

The fine-structure is a [chain of equidistant dots](#) with a spacing of approx. 1/2 the line width. The line width is constant along the laser line. Across the laser line the intensity distribution is approx. Gaussian.

The laser has integrated electronics [type P](#) with micro-controller for control of the laser output power. The output power can be controlled using the [modulation input ports \(TTL and analog\)](#) or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance.

A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

13LRM25-M125-1.5+55CM-660-60-M25-T12-P-6

Series	13LRM	
Order Code	13LRM25-M125-1.5+55CM-660-60-M25-T12-P-6	
Line profile	Constant Intensity Distribution	
Line type	Laser Macro Line	
Wavelength	660 +4/-6 nm	
Laser output power	60 mW	
Laser safety class	3B	
Fan angle α	25 deg	
Focussing range	95-195 mm	
Working distance	111 mm	
Line length	55 mm	
Line width	0.079 mm	
Depth of focus	20.4 mm	
Edge intensity	80 %	
Diameter laser module	25/28 mm	
Module length	86.8 mm	
Installation length	227.8 mm	
Cable length	1.5 m	
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 \pm 0.2 V	
Max. current consumption	0.25 A	
Working temperature	15 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	9 kOhm	9 kOhm
Max. modulation frequency	0.01 kHz	250 kHz
Modulation delay ON/OFF	3000/3000 μ s	0.5/0.2 μ s
Rise / Fall time	40000/40000 μ s	0.5/0.5 μ s

DOWNLOADS

[930412000124.pdf](#)

ACCESSORIES

50HD-15	Hex key WS 1.5
9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile
PS051003E	Power Supply 5 V

RELATED PRODUCTS

LASER MODULES SERIES 13LR	<ul style="list-style-type: none">▪ Micro Line Generator, fan angle▪ Uniform intensity distribution
LASER MODULES SERIES 13LNM	<ul style="list-style-type: none">▪ Micro Line Generator, small fan angle▪ Uniform intensity distribution▪ Extended depth of focus
LASER MODULES SERIES 5LMM+25CM	<ul style="list-style-type: none">▪ Compact Micro Line, small fan angle▪ Gaussian intensity distribution▪ Extended depth of focus
LASER MODULES SERIES 5LPM+25CM	<ul style="list-style-type: none">▪ Compact Macro Line, large fan angle▪ Gaussian intensity distribution▪ Extended depth of focus
LASER MODULES SERIES 5LMM	<ul style="list-style-type: none">▪ Macro Line, small fan angle▪ Gaussian intensity distribution▪ Extended depth of focus
LASER MODULES SERIES 5LPM	<ul style="list-style-type: none">▪ Macro Line, large fan angle▪ Gaussian intensity distribution▪ Extended depth of focus

This is a printout of the page https://sukhamburg.com/products/details/13LRM25-M125-1_5_55CM-660-60-M25-T12-P-6 from 4/19/2024

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)