13LRM40-M125-1.5+55CM-405-8-Y07-T15-C-6

Laser Macro Line Generator with a fan angle



FEATURES

Laser line with a fan angle, approx. uniform intensity distributionand extended depth of focus.

- Line length: 0 mm
- Line width: 49 μm
- Wavelength: 405 nm
- Working distance: 111 mm
- Depth of focus: 12.5 mm
- Macro Line Generator for extended depth of focus



DESCRIPTION

The laser diode beam source type 13LRM40-M125-1.5+55CM-405-8-Y07-T15-C-6 has a fan angle of 40° with a constant line width and approx. uniform intensity distribution along the laser line as well an extended depth of focus.

The fine-structure is a <u>chain of equidistant dots</u> with a spacing of approx. 1/2 the line width. The line width is constant along the laser line. Across the laser line the intensity distribution is approx. Gaussian.

The laser has integrated electronics <u>type C</u> for control of the laser output power. The output power can be controlled using the <u>modulation input ports (TTL and analog)</u> or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance.



A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

13LRM40-M125-1.5+55CM-405-8-Y07-T15-C-6

Series		13LRM
Order Code	13LRM40-M125-1.5+55CM-405-8-Y07-T15-C-6	
Line profile	Constant Intensity Distribution	
Line type	Laser Macro Line	
Wavelength	405 +5/-5 nm	
Laser output power	8 mW	
Laser safety class	3В	
Fan angle α	40 deg	
Focussing range	95-195 mm	
Working distance		111 mm
Line length		0 mm
Line width	0.049 mm	
Depth of focus	12.5 mm	
Edge intensity	80 %	
Diameter laser module	25/28 mm	
Module length	91.3 mm	
Installation length	232.3 mm	
Cable length		1.5 m
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 ± 0.2 V	
Max. current consumption		0.5 A
Working temperature	0 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	22 kOhm	22 kOhm
Max. modulation frequency	100 kHz	100 kHz
Modulation delay ON/OFF	1/0.5 µs	2/1 µs
Rise / Fall time	3/2 µs	3/2 µs

DOWNLOADS



13LRM+55CM+234.pdf

ACCESSORIES

50HD-15	Hex key WS 1.5
9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile
PS051003E	Power Supply 5 V

RELATED PRODUCTS

LASER MODULES SERIES 13LR	 Micro Line Generator, fan angle Uniform intensity distribution
LASER MODULES SERIES 13LNM	 Micro Line Generator, small fan angle Uniform intensity distribution Extended depth of focus
LASER MODULES SERIES 5LMM+25CM	 Compact Micro Line, small fan angle Gaussian intensity distribution Extended depth of focus
LASER MODULES SERIES 5LPM+25CM	 Compact Macro Line, large fan angle Gaussian intensity distribution Extended depth of focus
LASER MODULES SERIES 5LMM	 Macro Line, small fan angle Gaussian intensity distribution Extended depth of focus
LASER MODULES SERIES 5LPM	 Macro Line, large fan angle Gaussian intensity distribution Extended depth of focus



DATA SHEET

This is a printout of the page <u>https://sukhamburg.com/products/details/13LRM40-M125-1_5_55CM-405-8-Y07-T15-C-6</u> from 5/7/2024

CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]

