

13LRM40-M125-1.5+55CM-640-16-H22-T15-C-6

Laser Macro Line Generator with a fan angle



FEATURES

Laser line with a fan angle, approx. uniform intensity distributionand extended depth of focus.

Line length: 0 mm
Line width: 77 μm
Wavelength: 640 nm
Working distance: 111 mm
Depth of focus: 19.8 mm

Macro Line Generator for extended depth of focus



DESCRIPTION

The laser diode beam source type 13LRM40-M125-1.5+55CM-640-16-H22-T15-C-6 has a fan angle of 40° with a constant line width and approx. uniform intensity distribution along the laser line as well an extended depth of focus.

The fine-structure is a <u>chain of equidistant dots</u> with a spacing of approx. 1/2 the line width. The line width is constant along the laser line. Across the laser line the intensity distribution is approx. Gaussian.

The laser has integrated electronics $\underline{type\ C}$ for control of the laser output power. The output power can be controlled using the $\underline{modulation\ input\ ports\ (TTL\ and\ analog)}$ or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance.



A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

13LRM40-M125-1.5+55CM-640-16-H22-T15-C-6

Line profile Constant Intensity Distribution Line type Laser Macro Line Wavelength 640 +5/-5 nm Laser output power 16 mW Laser safety class 3E Fan angle α 40 deg Focussing range 95-195 mm Working distance 111 mm Line length 0 mm Line width 0.077 mm Depth of focus 19.8 mm Edge intensity 80 % Diameter laser module 25/28 mm Module length 91.3 mm Installation length 232.3 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.2 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz	Series 13LRM			
Line type Laser Macro Line Wavelength 640 +5/-5 nm Laser output power 16 mW Laser safety class 3E Fan angle α 40 deg Focussing range 95-195 mm Working distance 111 mm Line length 0 mm Line width 0.077 mm Depth of focus 19.8 mm Edge intensity 80 % Diameter laser module 25/28 mm Module length 91.3 mm Installation length 232.3 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.2 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz	Order Code	13LRM40-M125-1.5+55CM-640-16-H22-T15-C-6		
Wavelength 640 +5/-5 nm Laser output power 16 mW Laser safety class 3E Fan angle α 40 deg Focussing range 95-195 mm Working distance 111 mm Line length 0 mm Line width 0.077 mm Depth of focus 19.8 mm Edge intensity 80 % Diameter laser module 25/28 mm Module length 91.3 mm Installation length 232.3 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.2 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz	Line profile	Constant Intensity Distribution		
Laser output power 16 mW Laser safety class 3E Fan angle α 40 deg Focussing range 95-195 mm Working distance 111 mm Line length 0 mm Line width 0.077 mm Depth of focus 19.8 mm Edge intensity 80 % Diameter laser module 25/28 mm Module length 91.3 mm Installation length 232.3 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.2 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz	Line type	Laser Macro Line		
Laser safety class 3E Fan angle α 40 deg Focussing range 95-195 mm Working distance 111 mm Line length 0 mm Line width 0.077 mm Depth of focus 19.8 mm Edge intensity 80 % Diameter laser module 25/28 mm Module length 91.3 mm Installation length 232.3 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.2 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz	Wavelength	640 +5/-5 nm		
Fan angle α 40 deg Focussing range 95-195 mm Working distance 111 mm Line length 0 mm Line width 0.077 mm Depth of focus 19.8 mm Edge intensity 80 % Diameter laser module 25/28 mm Module length 91.3 mm Installation length 232.3 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.2 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz	Laser output power	16 mW		
Focussing range 95-195 mm Working distance 111 mm Line length 0 mm Line width 0.077 mm Depth of focus 19.8 mm Edge intensity 80 % Diameter laser module 25/28 mm Module length 91.3 mm Installation length 232.3 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.2 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz	Laser safety class	3В		
Working distance111 mmLine length0 mmLine width0.077 mmDepth of focus19.8 mmEdge intensity80 %Diameter laser module25/28 mmModule length91.3 mmInstallation length232.3 mmCable length1.5 mConnector typeLumberg SV50 IEC 61076-2-106Supply voltage5 ± 0.2 VMax. current consumption0.25 AWorking temperature0 - 40 °CModulation inputsAnalogTTLInput resistance22 kOhm22 kOhmMax. modulation frequency100 kHz100 kHz	Fan angle α	40 deg		
Line length 0 mm Line width 0.077 mm Depth of focus 19.8 mm Edge intensity 80 % Diameter laser module 25/28 mm Module length 91.3 mm Installation length 232.3 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.2 V Max. current consumption 0.25 A Working temperature 0 - 40 ° C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz	Focussing range	95-195 mm		
Line width0.077 mmDepth of focus19.8 mmEdge intensity80 %Diameter laser module25/28 mmModule length91.3 mmInstallation length232.3 mmCable length1.5 mConnector typeLumberg SV50 IEC 61076-2-106Supply voltage5 ± 0.2 VMax. current consumption0.25 AWorking temperature0 - 40 °CModulation inputsAnalogTTLInput resistance22 kOhm22 kOhmMax. modulation frequency100 kHz100 kHz	Working distance	111 mm		
Depth of focus 19.8 mm Edge intensity 80 % Diameter laser module 25/28 mm Module length 91.3 mm Installation length 232.3 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.2 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz	Line length	0 mm		
Edge intensity80 %Diameter laser module25/28 mmModule length91.3 mmInstallation length232.3 mmCable length1.5 mConnector typeLumberg SV50 IEC 61076-2-106Supply voltage5 ± 0.2 VMax. current consumption0.25 AWorking temperature0 - 40 °CModulation inputsAnalogTTLInput resistance22 kOhm22 kOhmMax. modulation frequency100 kHz100 kHz	Line width	0.077 mm		
Diameter laser module25/28 mmModule length91.3 mmInstallation length232.3 mmCable length1.5 mConnector typeLumberg SV50 IEC 61076-2-106Supply voltage5 ± 0.2 VMax. current consumption0.25 AWorking temperature0 - 40 °CModulation inputsAnalogTTLInput resistance22 kOhm22 kOhmMax. modulation frequency100 kHz100 kHz	Depth of focus	19.8 mm		
Module length91.3 mmInstallation length232.3 mmCable length1.5 mConnector typeLumberg SV50 IEC 61076-2-106Supply voltage5 ± 0.2 VMax. current consumption0.25 AWorking temperature0 - 40 °CModulation inputsAnalogTTLInput resistance22 kOhm22 kOhmMax. modulation frequency100 kHz100 kHz	Edge intensity	80 %		
Installation length Cable length Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.2 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz	Diameter laser module	25/28 mm		
Cable length1.5 mConnector typeLumberg SV50 IEC 61076-2-106Supply voltage5 ± 0.2 VMax. current consumption0.25 AWorking temperature0 - 40 °CModulation inputsAnalogTTLInput resistance22 kOhm22 kOhmMax. modulation frequency100 kHz100 kHz	Module length	91.3 mm		
Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz	Installation length	232.3 mm		
Supply voltage $5 \pm 0.2 \mathrm{M}$ Max. current consumption $0.25 \mathrm{A}$ Working temperature $0 - 40 \mathrm{^{\circ}C}$ Modulation inputsAnalogTTLInput resistance $22 \mathrm{kOhm}$ $22 \mathrm{kOhm}$ Max. modulation frequency $100 \mathrm{kHz}$ $100 \mathrm{kHz}$	Cable length	1.5 m		
Max. current consumption0.25 AWorking temperature0 - 40 °CModulation inputsAnalogTTLInput resistance22 kOhm22 kOhmMax. modulation frequency100 kHz100 kHz	Connector type	Lumberg SV50 IEC 61076-2-106		
Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz	Supply voltage	5 ± 0.2 V		
Modulation inputsAnalogTTLInput resistance22 kOhm22 kOhmMax. modulation frequency100 kHz100 kHz	Max. current consumption	0.25 A		
Input resistance22 kOhm22 kOhmMax. modulation frequency100 kHz100 kHz	Working temperature		0 - 40 °C	
Max. modulation frequency 100 kHz 100 kHz	Modulation inputs	Analog	TTL	
	Input resistance	22 kOhm	22 kOhm	
Modulation delay ON/OFF1/0.5 μs2/1 μs	Max. modulation frequency	100 kHz	100 kHz	
	Modulation delay ON/OFF	1/0.5 μs	2/1 μs	
Rise / Fall time 3/2 μs 3/2 μs	Rise / Fall time	3/2 μs	3/2 µs	



DOWNLOADS



ACCESSORIES

50HD-15 Hex key WS 1.5

9D-12 Screwdriver WS 1.2

13MK-25-36-10-F Mounting Console with flat base plate

13MK-25-36-10-M Mounting Console with base plate with dovetail

profile

PS051003E Power Supply 5 V

RELATED PRODUCTS

LASER MODULES SERIES 13LR Micro Line Generator, fan angle

Uniform intensity distribution

LASER MODULES SERIES 13LNM ■ Micro Line Generator, small fan angle

Uniform intensity distribution

Extended depth of focus

LASER MODULES SERIES 5LMM+25CM ■ Compact Micro Line, small fan angle

Gaussian intensity distribution

Extended depth of focus

LASER MODULES SERIES 5LPM+25CM Compact Macro Line, large fan angle

Gaussian intensity distribution

Extended depth of focus

LASER MODULES SERIES 5LMM Macro Line, small fan angle

Gaussian intensity distribution

Extended depth of focus

LASER MODULES SERIES 5LPM Macro Line, large fan angle

Gaussian intensity distribution

Extended depth of focus



This is a printout of the page https://sukhamburg.com/products/details/13LRM40-M125-1 5 55CM-640-16-H22-T15-C-6 from 5/4/2024

CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany

Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]