

13LRM40-S250-1.5+55CM-639-13-H18-T12-C-6

Laser Macro Line Generator with a fan angle



FEATURES

Laser line with a fan angle, approx. uniform intensity distribution and extended depth of focus.

- Line length: 180 mm
- Line width: 155 μm
- Wavelength: 639 nm
- Working distance: 240 mm
- Depth of focus: 79.1 mm

- Macro Line Generator for extended depth of focus



DESCRIPTION

The laser diode beam source type 13LRM40-S250-1.5+55CM-639-13-H18-T12-C-6 has a fan angle of 40° with a constant line width and approx. uniform intensity distribution along the laser line as well as an extended depth of focus.

The fine-structure is a [chain of equidistant dots](#) with a spacing of approx. 1/2 the line width. The line width is constant along the laser line. Across the laser line the intensity distribution is approx. Gaussian.

The laser has integrated electronics [type C](#) for control of the laser output power. The output power can be controlled using the [modulation input ports \(TTL and analog\)](#) or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance.

A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

13LRM40-S250-1.5+55CM-639-13-H18-T12-C-6

| | | |
|---------------------------|--|-------------|
| Series | 13LRM | |
| Order Code | 13LRM40-S250-1.5+55CM-639-13-H18-T12-C-6 | |
| Line profile | Constant Intensity Distribution | |
| Line type | Laser Macro Line | |
| Wavelength | 639 +10/-10 nm | |
| Laser output power | 13 mW | |
| Laser safety class | 3B | |
| Fan angle α | 40 deg | |
| Focussing range | 195-355 mm | |
| Working distance | 240 mm | |
| Line length | 180 mm | |
| Line width | 0.155 mm | |
| Depth of focus | 79.1 mm | |
| Edge intensity | 80 % | |
| Diameter laser module | 25/28 mm | |
| Module length | 86.8 mm | |
| Installation length | 356.8 mm | |
| Cable length | 1.5 m | |
| Connector type | Lumberg SV50 IEC 61076-2-106 | |
| Supply voltage | 5 \pm 0.2 V | |
| Max. current consumption | 0.25 A | |
| Working temperature | 0 - 40 °C | |
| Modulation inputs | Analog | TTL |
| Input resistance | 22 kOhm | 22 kOhm |
| Max. modulation frequency | 100 kHz | 100 kHz |
| Modulation delay ON/OFF | 1/0.5 μ s | 2/1 μ s |
| Rise / Fall time | 3/2 μ s | 3/2 μ s |

DOWNLOADS

[930412000124.pdf](#)

ACCESSORIES

| | |
|-----------------|--|
| 50HD-15 | Hex key WS 1.5 |
| 9D-12 | Screwdriver WS 1.2 |
| 13MK-25-36-10-F | Mounting Console with flat base plate |
| 13MK-25-36-10-M | Mounting Console with base plate with dovetail profile |
| PS051003E | Power Supply 5 V |

RELATED PRODUCTS

| | |
|-----------------------------------|---|
| LASER MODULES SERIES 13LR | <ul style="list-style-type: none">▪ Micro Line Generator, fan angle▪ Uniform intensity distribution |
| LASER MODULES SERIES 13LNM | <ul style="list-style-type: none">▪ Micro Line Generator, small fan angle▪ Uniform intensity distribution▪ Extended depth of focus |
| LASER MODULES SERIES 5LMM+25CM | <ul style="list-style-type: none">▪ Compact Micro Line, small fan angle▪ Gaussian intensity distribution▪ Extended depth of focus |
| LASER MODULES SERIES 5LPM+25CM | <ul style="list-style-type: none">▪ Compact Macro Line, large fan angle▪ Gaussian intensity distribution▪ Extended depth of focus |
| LASER MODULES SERIES 5LMM | <ul style="list-style-type: none">▪ Macro Line, small fan angle▪ Gaussian intensity distribution▪ Extended depth of focus |
| LASER MODULES SERIES 5LPM | <ul style="list-style-type: none">▪ Macro Line, large fan angle▪ Gaussian intensity distribution▪ Extended depth of focus |

This is a printout of the page https://sukhamburg.com/products/details/13LRM40-S250-1_5_55CM-639-13-H18-T12-C-6 from 5/3/2024

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)