

13LT-4000+90CM-450-28-O06-M60-PS-7

Semi-telecentric Micro Line Generator




FEATURES

Semi-telecentric laser line with constant line length 15mm and approx. uniform intensity distribution.

- Line length: 15 mm
- Line width: 172 μ m
- Wavelength: 450 nm
- Working distance: 3993 mm

- Micro Line Generator for small laser line widths and high power density in the focal plane
- With RS232 interface



DESCRIPTION

The laser diode beam source type 13LT-4000+90CM-450-28-O06-M60-PS-7 produces a semi-telecentric laser line with 15 mm line length. The intensity profile is approx. uniform in line direction. More precisely, it is Gaussian clipped by an aperture with an edge intensity of 75 %. The line width is constant along the laser line. Across the laser line the intensity distribution is Gaussian.

The laser has integrated electronics [type PS](#) with micro-controller for control of the laser output power and serial interface (RS232). The output power can be controlled using the [modulation input ports \(TTL and analog\)](#), or manually using the potentiometer.


For this laser type the working distance is fixed. A fine-adjustment of the distance between laser and target is recommended for fine-focusing in order to achieve minimal line width.

TECHNICAL DATA

13LT-4000+90CM-450-28-O06-M60-PS-7

| | | |
|----------------------------------|------------------------------------|------------|
| Series | 13LT | |
| Order Code | 13LT-4000+90CM-450-28-O06-M60-PS-7 | |
| Line profile | Constant Intensity Distribution | |
| Line type | Laser Micro Line | |
| Wavelength | 450 +10/-10 nm | |
| Laser output power | 28 mW | |
| Laser safety class | 3B | |
| Focussing range | 3993-3993 mm | |
| Working distance | 3993 mm | |
| Line length | 15 mm | |
| Line width | 0.172 mm | |
| Rayleigh range | 103 mm | |
| Edge intensity | 75 % | |
| Diameter laser module | 25/28 mm | |
| Module length | 121.9 mm | |
| Installation length | 4144.9 mm | |
| Cable length | 1.5 m | |
| Connector type | Lumberg SV70 IEC 61076-2-106 | |
| Supply voltage | 5 ± 0.2 V | |
| Max. current consumption | 0.5 A | |
| Working temperature | 15 - 40 °C | |
| Modulation inputs | Analog | TTL |
| Input resistance | 9 kOhm | 9 kOhm |
| Max. modulation frequency | 0.001 kHz | 250 kHz |
| Modulation delay ON/OFF | 3000/3000 µs | 0.6/0.2 µs |
| Rise / Fall time | 200000/200000 µs | 0.2/0.2 µs |
| Interface | RS232 | |

Dimensions (for a complete dimensional drawing please refer to the downloads section)



DOWNLOADS



[951210000053.pdf](#)

ACCESSORIES

9D-12

Screwdriver WS 1.2

PS051007E

Power Supply 5 V for laser modules with RS232 interface

RELATED PRODUCTS

**LASER MODULES
SERIES 13LTM**

- Semi-telecentric Macro Line
- Uniform intensity distribution
- Constant line length **15 mm**
- Extended depth of focus

**LASER MODULES
SERIES
LNC-13LT**

- Semi-telecentric Micro Line
- Uniform intensity distribution
- Constant line length **15 mm**
- Low noise

**LASER MODULES
SERIES 5LT-1+25CM**

- **Compact** semi-telecentric Micro Line
- Gaussian intensity distribution
- Constant line length ca. **4.8 mm**

LASER MODULES
SERIES 5LT-2+25CM

- **Compact** semi-telecentric Micro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**

LASER MODULES
SERIES 5LT-1

- Semi-telecentric Micro Line
- Gaussian intensity distribution
- Constant line length ca. **4.8 mm**

LASER MODULES
SERIES 5LT-2

- Semi-telecentric Micro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**

This is a printout of the page https://sukhamburg.com/products/details/13LT-4000_90CM-450-28-O06-M60-PS-7 from 4/25/2024

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)