

## 13LTM-500-41+90CM-685-7-H13-M60-C-6

Semi-telecentric Macro Line Generator Semi-telecentric Macro Line Generator




### FEATURES

Semi-telecentric laser line with constant line length 15mm, approx. uniform intensity distribution and extended depth of focus.

- Line length: 15 mm
- Line width: 124  $\mu\text{m}$
- Wavelength: 685 nm
- Working distance: 488 mm
- Depth of focus: 47.7 mm

- Macro Line Generator for extended depth of focus



## DESCRIPTION

The laser diode beam source type 13LTM-500-41+90CM-685-7-H13-M60-C-6 produces a semi-telecentric laser line with 15 mm line length and extended depth of focus. The intensity profile is approx. uniform in line direction. More precisely, it is Gaussian clipped by an aperture with an edge intensity of 75 %. The line width is constant along the laser line. Across the laser line the intensity distribution is approx. Gaussian.

The laser has integrated electronics [type C](#) for control of the laser output power. The output power can be controlled using the [modulation input ports \(TTL and analog\)](#), or manually using the potentiometer.

For this laser type the working distance is fixed. A fine-adjustment of the distance between laser and target is recommended for fine-focusing in order to achieve minimal line width.

**TECHNICAL DATA**

13LTM-500-41+90CM-685-7-H13-M60-C-6

<b>Series</b>	13LTM	
<b>Order Code</b>	13LTM-500-41+90CM-685-7-H13-M60-C-6	
<b>Line profile</b>	Constant Intensity Distribution	
<b>Line type</b>	Laser Macro Line	
<b>Wavelength</b>	685 +10/-10 nm	
<b>Laser output power</b>	7 mW	
<b>Laser safety class</b>	3B	
<b>Focussing range</b>	488-488 mm	
<b>Working distance</b>	488 mm	
<b>Line length</b>	15 mm	
<b>Line width</b>	0.124 mm	
<b>Depth of focus</b>	47.7 mm	
<b>Edge intensity</b>	75 %	
<b>Diameter laser module</b>	25/28 mm	
<b>Module length</b>	127.3 mm	
<b>Installation length</b>	645.3 mm	
<b>Cable length</b>	1.5 m	
<b>Connector type</b>	Lumberg SV50 IEC 61076-2-106	
<b>Supply voltage</b>	5 ± 0.2 V	
<b>Max. current consumption</b>	0.25 A	
<b>Working temperature</b>	0 - 40 °C	
<b>Modulation inputs</b>	Analog	TTL
<b>Input resistance</b>	22 kOhm	22 kOhm
<b>Max. modulation frequency</b>	100 kHz	100 kHz
<b>Modulation delay ON/OFF</b>	1/0.5 µs	2/1 µs
<b>Rise / Fall time</b>	3/2 µs	3/2 µs



**LASER MODULES**  
**SERIES 5LTM-2+25CM**

- **Compact** semi-telecentric Macro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**
- Extended depth of focus

**LASER MODULES**  
**SERIES 5LTM-1**

- Semi-telecentric Macro Line
- Gaussian intensity distribution
- Constant line length ca. **4.8 mm**
- Extended depth of focus

**LASER MODULES**  
**SERIES 5LTM-2**

- Semi-telecentric Macro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**
- Extended depth of focus

This is a printout of the page [https://sukhamburg.com/products/details/13LTM-500-41\\_90CM-685-7-H13-M60-C-6](https://sukhamburg.com/products/details/13LTM-500-41_90CM-685-7-H13-M60-C-6) from 6/4/2023

## CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH  
Kieler Str. 212  
22525 Hamburg  
Germany  
Tel: +49 40 85 39 97-0  
Fax: +49 40 85 39 97-79

[info@sukhamburg.de](mailto:info@sukhamburg.de)  
[www.sukhamburg.com](http://www.sukhamburg.com)

## LEGAL NOTICE

**Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.**

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)