

### 13M-M125+55CM-405-15-Y07-T15-C-6

Laser Micro Focus Generator with elliptical Gaussian beam profile



#### **FEATURES**

Laser spot with elliptical Gaussian beam profile.

Spot diameter: 0.008 x 0.017 mm

Wavelength: 405 nmWorking distance: 120 mm

 Micro Focus Generator for small spot widths and high power density in the focal plane



### **DESCRIPTION**

The laser diode beam source type 13M-M125+55CM-405-15-Y07-T15-C-6 produces an elliptical laser spot with elliptical Gaussian intensity distribution.

The laser has integrated electronics  $\underline{type\ C}$  for control of the laser output power. The output power can be controlled using the  $\underline{modulation\ input\ ports\ (TTL\ and\ analog)}}$  or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that the spot diameter increases proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

### **TECHNICAL DATA**

13M-M125+55CM-405-15-Y07-T15-C-6

Series 13M

Order Code 13M-M125+55CM-405-15-Y07-T15-C-6



Line profile	Gaussian Intensity Distribution	
Wavelength	405 +5/-5 nm	
Laser output power	15 mW	
Laser safety class	3B	
Focussing range	110-205 mm	
Working distance	120 mm	
Spot height	0.017 mm	
Spot width	0.008 mm	
Rayleigh range	0.232 mm	
Diameter laser module	25/28 mm	
Module length	75.9 mm	
Installation length	225.9 mm	
Cable length	1.5 m	
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 ± 0.2 V	
Max. current consumption	0.5 A	
Working temperature	0 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	22 kOhm	22 kOhm
Max. modulation frequency	100 kHz	100 kHz
Modulation delay ON/OFF	1/0.5 μs	2/1 μs
Rise / Fall time	3/2 μs	3/2 μs

# **ACCESSORIES**

**50HD-15** Hex key WS 1.5

**9D-12** Screwdriver WS 1.2

**13MK-25-36-10-F** Mounting Console with flat base plate

13MK-25-36-10-M Mounting Console with base plate with dovetail

profile

PS051003E Power Supply 5 V

## **RELATED PRODUCTS**



LASER MODULES

**SERIES 13MM** 

Macro Focus Generator

Circular beam profile

Extended depth of focus

LASER MODULES

Micro Focus Generator

**SERIES 13MC** 

Rotationally symmetric, Gaussian beam profile

LASER MODULES

Micro Focus Generator

SERIES LNC-13M • Elliptical Gaussian beam profile

Low noise

LASER MODULES

Compact Laser Micro Focus Generator

SERIES 5MC

Rotationally symmetric, Gaussian beam profile

LASER MODULES

Compact Laser Micro Focus Generator

**SERIES 5M** 

Elliptical Gaussian beam profile

This is a printout of the page <a href="https://sukhamburg.com/products/details/13M-M125">https://sukhamburg.com/products/details/13M-M125</a> 55CM-405-15-Y07-T15-C-6 from 5/5/2024

#### CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212 22525 Hamburg Germany

Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

### **LEGAL NOTICE**

### Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]