

## 13M-M60+55CM-405-15-Y07-T15-C-6

Laser Micro Focus Generator with elliptical Gaussian beam profile




### FEATURES

Laser spot with elliptical Gaussian beam profile.

- Spot diameter: 0.004 x 0.008 mm
- Wavelength: 405 nm
- Working distance: 54 mm

- Micro Focus Generator for small spot widths and high power density in the focal plane



## DESCRIPTION

The laser diode beam source type 13M-M60+55CM-405-15-Y07-T15-C-6 produces an elliptical laser spot with elliptical Gaussian intensity distribution.

The laser has integrated electronics [type C](#) for control of the laser output power. The output power can be controlled using the [modulation input ports \(TTL and analog\)](#), or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that the spot diameter increases proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

## TECHNICAL DATA

13M-M60+55CM-405-15-Y07-T15-C-6

Series	13M
Order Code	13M-M60+55CM-405-15-Y07-T15-C-6

Line profile	Gaussian Intensity Distribution	
Wavelength	405 +5/-5 nm	
Laser output power	15 mW	
Laser safety class	3B	
Focussing range	40-80 mm	
Working distance	54 mm	
Spot height	0.008 mm	
Spot width	0.004 mm	
Rayleigh range	0.053 mm	
Diameter laser module	25/28 mm	
Module length	75.9 mm	
Installation length	159.9 mm	
Cable length	1.5 m	
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 ± 0.2 V	
Max. current consumption	0.5 A	
Working temperature	0 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	22 kOhm	22 kOhm
Max. modulation frequency	100 kHz	100 kHz
Modulation delay ON/OFF	1/0.5 µs	2/1 µs
Rise / Fall time	3/2 µs	3/2 µs

## ACCESSORIES

50HD-15	Hex key WS 1.5
9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile
PS051003E	Power Supply 5 V

## RELATED PRODUCTS

**LASER MODULES  
SERIES 13MM**

- Macro Focus Generator
- **Circular** beam profile
- Extended depth of focus

**LASER MODULES  
SERIES 13MC**

- Micro Focus Generator
- **Rotationally symmetric**, Gaussian beam profile

**LASER MODULES  
SERIES LNC-13M**

- Micro Focus Generator
- Elliptical Gaussian beam profile
- Low noise

**LASER MODULES  
SERIES 5MC**

- **Compact** Laser Micro Focus Generator
- **Rotationally symmetric**, Gaussian beam profile

**LASER MODULES  
SERIES 5M**

- **Compact** Laser Micro Focus Generator
- Elliptical Gaussian beam profile

This is a printout of the page [https://sukhamburg.com/products/details/13M-M60\\_55CM-405-15-Y07-T15-C-6](https://sukhamburg.com/products/details/13M-M60_55CM-405-15-Y07-T15-C-6) from 5/6/2024

## CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

[info@sukhamburg.de](mailto:info@sukhamburg.de)

[www.sukhamburg.com](http://www.sukhamburg.com)

## LEGAL NOTICE

**Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.**

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)