#### 13M-M60+55CM-635-10-H10-T15-CS-7

Laser Micro Focus Generator with elliptical Gaussian beam profile



#### FEATURES

Laser spot with elliptical Gaussian beam profile.

- Spot diameter: 0.004 x 0.014 mm
- Wavelength: 635 nm
- Working distance: 54 mm
- Micro Focus Generator for small spot widths and high power density in the focal plane
- With RS232 interface



#### DESCRIPTION

The laser diode beam source type 13M-M60+55CM-635-10-H10-T15-CS-7 produces an elliptical laser spot with elliptical Gaussian intensity distribution.

The laser has integrated electronics <u>type CS</u> for control of the laser output power and serial interface (RS232). The output power can be controlled using the <u>modulation input</u> <u>ports (TTL and analog)</u> or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that the spot diameter increases proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

## **TECHNICAL DATA**

13M-M60+55CM-635-10-H10-T15-CS-7

Series

13M



Order Code	13M-M60+55CM-635-10-H10-T15-CS-7	
Line profile	e profile Gaussian Intensity Distribution	
Wavelength	635 +10/-10 nm	
Laser output power	10 mW	
Laser safety class		3B
Focussing range	40-80 mm	
Working distance		54 mm
Spot height		0.014 mm
Spot width	0.004 mm	
Rayleigh range	0.04 mm	
Diameter laser module	25/28 mm	
Module length	75.9 mm	
Installation length	159.9 mm	
Cable length	1.5 m	
Connector type	Lumberg SV70 IEC 61076-2-106	
Supply voltage	5 ± 0.2 V	
Max. current consumption	0.25A	
Working temperature		0 - 40 °C
Modulation inputs	Analog	TTL
Input resistance	9 kOhm	9 kOhm
Max. modulation frequency	0.001 kHz	250 kHz
Modulation delay ON/OFF	3000/3000 µs	0.5/0.2 μs
Rise / Fall time	200000/200000 µs	0.8/0.4 μs
Interface		RS232

## ACCESSORIES

50HD-15	Hex key WS 1.5
9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile



PS051007E	Power Supply 5 V for laser modules with RS232 interface	
RELATED PRODUCTS		
LASER MODULES SERIES 13MM	<ul> <li>Macro Focus Generator</li> <li>Circular beam profile</li> <li>Extended depth of focus</li> </ul>	
LASER MODULES SERIES 13MC	<ul> <li>Micro Focus Generator</li> <li>Rotationally symmetric, Gaussian beam profile</li> </ul>	
LASER MODULES SERIES LNC-13M	<ul> <li>Micro Focus Generator</li> <li>Elliptical Gaussian beam profile</li> <li>Low noise</li> </ul>	
LASER MODULES SERIES 5MC	<ul> <li>Compact Laser Micro Focus Generator</li> <li>Rotationally symmetric, Gaussian beam profile</li> </ul>	
LASER MODULES SERIES 5M	<ul> <li>Compact Laser Micro Focus Generator</li> <li>Elliptical Gaussian beam profile</li> </ul>	

This is a printout of the page <u>https://sukhamburg.com/products/details/13M-M60\_55CM-635-10-H10-T15-CS-7</u> from 5/6/2024

### CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com



# **LEGAL NOTICE**

#### Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]

