

### 13M-M60+55CM-660-107-M25-T12-P-6

Laser Micro Focus Generator with elliptical Gaussian beam profile



#### **FEATURES**

Laser spot with elliptical Gaussian beam profile.

Spot diameter: 0.008 x 0.014 mm

Wavelength: 660 nmWorking distance: 54 mm

 Micro Focus Generator for small spot widths and high power density in the focal plane



### **DESCRIPTION**

The laser diode beam source type 13M-M60+55CM-660-107-M25-T12-P-6 produces an elliptical laser spot with elliptical Gaussian intensity distribution.

The laser has integrated electronics  $\underline{type\ P}$  with micro-controller for control of the laser output power. The output power can be controlled using the  $\underline{modulation\ input\ ports\ (TTL\ and\ analog)}$  or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that the spot diameter increases proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

### **TECHNICAL DATA**

13M-M60+55CM-660-107-M25-T12-P-6

Series 13M

Order Code 13M-M60+55CM-660-107-M25-T12-P-6



Line profile	Gaussian Intensity Distribution	
Wavelength	660 +4/-6 nm	
Laser output power	107 mW	
Laser safety class	3B	
Focussing range	40-80 mm	
Working distance	54 mm	
Spot height	0.014 mm	
Spot width	0.008 mm	
Rayleigh range	0.169 mm	
Diameter laser module	25/28 mm	
Module length	75.9 mm	
Installation length	159.9 mm	
Cable length	1.5 m	
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 ± 0.2 V	
Max. current consumption	0.25 A	
Working temperature	15 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	9 kOhm	9 kOhm
Max. modulation frequency	0.01 kHz	250 kHz
Modulation delay ON/OFF	3000/3000 μs	0.5/0.2 μs
Rise / Fall time	40000/40000 μs	0.5/0.5 μs

# **ACCESSORIES**

**50HD-15** Hex key WS 1.5

**9D-12** Screwdriver WS 1.2

**13MK-25-36-10-F** Mounting Console with flat base plate

13MK-25-36-10-M Mounting Console with base plate with dovetail

profile

PS051003E Power Supply 5 V

## **RELATED PRODUCTS**



LASER MODULES

SERIES 13MM

Macro Focus Generator

• Circular beam profile

Extended depth of focus

LASER MODULES SERIES 13MC Micro Focus Generator

• Rotationally symmetric, Gaussian beam profile

LASER MODULES SERIES LNC-13M Micro Focus Generator

Elliptical Gaussian beam profile

Low noise

LASER MODULES

**SERIES 5MC** 

Compact Laser Micro Focus Generator

Rotationally symmetric, Gaussian beam profile

LASER MODULES

Compact Laser Micro Focus Generator

SERIES 5M • Elliptical Gaussian beam profile

This is a printout of the page <a href="https://sukhamburg.com/products/details/13M-M60">https://sukhamburg.com/products/details/13M-M60</a> 55CM-660-107-M25-T12-P-6 from 5/5/2024

#### CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212 22525 Hamburg Germany

Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

### **LEGAL NOTICE**

### Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]