#### 13M-S000+55CM-520-60-O11-T15-P-6


Laser Micro Focus Generator with elliptical Gaussian beam profile



#### **FEATURES**

Laser spot with elliptical Gaussian beam profile.

- Spot diameter: 0.135 x 0.481 mm
- Wavelength: 520 nm
- Working distance: 2000 mm
- Micro Focus Generator for small spot widths and high power density in the focal plane



#### DESCRIPTION

The laser diode beam source type 13M-S000+55CM-520-60-O11-T15-P-6 produces an elliptical laser spot with elliptical Gaussian intensity distribution.

The laser has integrated electronics <u>type P</u> with micro-controller for control of the laser output power. The output power can be controlled using the <u>modulation input ports (TTL and analog)</u> or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that the spot diameter increases proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

## **TECHNICAL DATA**

13M-S000+55CM-520-60-O11-T15-P-6

 Series
 13M

 Order Code
 13M-S000+55CM-520-60-O11-T15-P-6





#### **DATA SHEET**

Line profile	Gaussian Intensity Distribution	
Wavelength	520 +10/-5 nm	
Laser output power	60 mW	
Laser safety class	3В	
Focussing range	1295-inf mm	
Working distance	2000 mm	
Spot height	0.481 mm	
Spot width	0.135 mm	
Rayleigh range	54.9 mm	
Diameter laser module	25/28 mm	
Module length	75.9 mm	
Installation length	2105.9 mm	
Cable length	1.5 m	
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 ± 0.2 V	
Max. current consumption	0.5 A	
Working temperature	15 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	9 kOhm	9 kOhm
Max. modulation frequency	0.01 kHz	250 kHz
Modulation delay ON/OFF	3000/3000 μs	0.5/0.2 μs
Rise / Fall time	40000/40000 μs	0.5/0.5 μs

# ACCESSORIES

50HD-15	Hex key WS 1.5
9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile
PS051003E	Power Supply 5 V

# **RELATED PRODUCTS**





LASER MODULES SERIES 13MM	<ul> <li>Macro Focus Generator</li> <li>Circular beam profile</li> <li>Extended depth of focus</li> </ul>
LASER MODULES SERIES 13MC	<ul> <li>Micro Focus Generator</li> <li>Rotationally symmetric, Gaussian beam profile</li> </ul>
LASER MODULES SERIES LNC-13M	<ul> <li>Micro Focus Generator</li> <li>Elliptical Gaussian beam profile</li> <li>Low noise</li> </ul>
LASER MODULES SERIES 5MC	<ul> <li>Compact Laser Micro Focus Generator</li> <li>Rotationally symmetric, Gaussian beam profile</li> </ul>
LASER MODULES SERIES 5M	<ul> <li>Compact Laser Micro Focus Generator</li> <li>Elliptical Gaussian beam profile</li> </ul>

This is a printout of the page <u>https://sukhamburg.com/products/details/13M-S000\_55CM-520-60-O11-T15-P-6</u> from 5/2/2024

## CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

## **LEGAL NOTICE**

#### Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]