

## 13M-S250+55CM-639-21-H18-T15-CS-7

Laser Micro Focus Generator with elliptical Gaussian beam profile




### FEATURES

Laser spot with elliptical Gaussian beam profile.

- Spot diameter: 0.017 x 0.057 mm
- Wavelength: 639 nm
- Working distance: 245 mm

- Micro Focus Generator for small spot widths and high power density in the focal plane
- With RS232 interface



## DESCRIPTION

The laser diode beam source type 13M-S250+55CM-639-21-H18-T15-CS-7 produces an elliptical laser spot with elliptical Gaussian intensity distribution.

The laser has integrated electronics [type CS](#) for control of the laser output power and serial interface (RS232). The output power can be controlled using the [modulation input ports \(TTL and analog\)](#) or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that the spot diameter increases proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

## TECHNICAL DATA

13M-S250+55CM-639-21-H18-T15-CS-7

Series

13M

Order Code	13M-S250+55CM-639-21-H18-T15-CS-7	
Line profile	Gaussian Intensity Distribution	
Wavelength	639 +10/-10 nm	
Laser output power	21 mW	
Laser safety class	3B	
Focussing range	205-410 mm	
Working distance	245 mm	
Spot height	0.057 mm	
Spot width	0.017 mm	
Rayleigh range	0.706 mm	
Diameter laser module	25/28 mm	
Module length	75.9 mm	
Installation length	350.9 mm	
Cable length	1.5 m	
Connector type	Lumberg SV70 IEC 61076-2-106	
Supply voltage	5 ± 0.2 V	
Max. current consumption	0.25 A	
Working temperature	0 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	9 kOhm	9 kOhm
Max. modulation frequency	0.001 kHz	250 kHz
Modulation delay ON/OFF	3000/3000 µs	0.5/0.2 µs
Rise / Fall time	200000/200000 µs	0.8/0.4 µs
Interface	RS232	

## ACCESSORIES

50HD-15	Hex key WS 1.5
9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile

PS051007E

Power Supply 5 V for laser modules with RS232 interface

## RELATED PRODUCTS

### LASER MODULES SERIES 13MM

- Macro Focus Generator
- **Circular** beam profile
- Extended depth of focus

### LASER MODULES SERIES 13MC

- Micro Focus Generator
- **Rotationally symmetric**, Gaussian beam profile

### LASER MODULES SERIES LNC-13M

- Micro Focus Generator
- Elliptical Gaussian beam profile
- Low noise

### LASER MODULES SERIES 5MC

- **Compact** Laser Micro Focus Generator
- **Rotationally symmetric**, Gaussian beam profile

### LASER MODULES SERIES 5M

- **Compact** Laser Micro Focus Generator
- Elliptical Gaussian beam profile

This is a printout of the page [https://sukhamburg.com/products/details/13M-S250\\_55CM-639-21-H18-T15-CS-7](https://sukhamburg.com/products/details/13M-S250_55CM-639-21-H18-T15-CS-7) from 4/19/2024

## CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

[info@sukhamburg.de](mailto:info@sukhamburg.de)

[www.sukhamburg.com](http://www.sukhamburg.com)

## LEGAL NOTICE

**Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.**

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)