13MC-S1000+95CM-635-10-B07-M60-CS-7


Laser Micro Focus Generator with rotationally symmetric beam profile



FEATURES

Laser spot with rotationally symmetric, Gaussian beam profile.

- Spot diameter: 0.057 x 0.057 mm
- Wavelength: 635 nm
- Working distance: 973 mm
- Micro Focus Generator for small spot widths and high power density in the focal plane
- With RS232 interface



DESCRIPTION

The laser diode beam source type 13MC-S1000+95CM-635-10-B07-M60-CS-7 produces a rotationally symmetric circular laser spot with Gaussian intensity distribution.

The laser has integrated electronics <u>type CS</u> for control of the laser output power and serial interface (RS232). The output power can be controlled using the <u>modulation input</u> <u>ports (TTL and analog)</u> or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that the spot diameter increases proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

13MC-S1000+95CM-635-10-B07-M60-CS-7



DATA SHEET

| Series 13MC | | |
|---------------------------|-------------------------------------|------------|
| Order Code | 13MC-S1000+95CM-635-10-B07-M60-CS-7 | |
| Line profile | Gaussian Intensity Distribution | |
| Wavelength | 635 +8/-8 nm | |
| Laser output power | 10 mW | |
| Laser safety class | 3В | |
| Focussing range | 815-1290 mm | |
| Working distance | 973 mm | |
| Spot height | 0.057 mm | |
| Spot width | 0.057 mm | |
| Rayleigh range | 8.02 mm | |
| Diameter laser module | 25/28 mm | |
| Module length | 121.9 mm | |
| Installation length | 1124.9 mm | |
| Cable length | 1.5 m | |
| Connector type | Lumberg SV70 IEC 61076-2-106 | |
| Supply voltage | 5 ± 0.2 V | |
| Max. current consumption | 0.25 A | |
| Working temperature | 0 - 40 °C | |
| Modulation inputs | Analog | TTL |
| Input resistance | 9 kOhm | 9 kOhm |
| Max. modulation frequency | 0.001 kHz | 250 kHz |
| Modulation delay ON/OFF | 3000/3000 μs | 0.5/0.2 μs |
| Rise / Fall time | 200000/200000 µs | 0.8/0.4 µs |
| nterface RS232 | | |

DOWNLOADS



13MC+95CM+80.pdf

ACCESSORIES

50HD-15

Hex key WS 1.5

9D-12

Screwdriver WS 1.2



| PS051007E | Power Supply 5 V for laser modules with RS232 interface | |
|----------------------------------|---|--|
| RELATED PRODUCTS | | |
| LASER MODULES SERIES 13MMC | Laser Macro Focus Generator Rotationally symmetric beam profile Extended depth of focus | |
| LASER MODULES SERIES LNC-13MC | Micro Focus Generator Rotationally symmetric, Gaussian beam profile Low noise | |
| LASER MODULES SERIES 13M | Micro Focus Generator Elliptical Gaussian beam profile | |
| LASER MODULES SERIES 5MC | Compact Laser Micro Focus Generator Rotationally symmetric, Gaussian beam profile | |
| LASER MODULES SERIES 5M | Compact Laser Micro Focus Generator Elliptical Gaussian beam profile | |

This is a printout of the page <u>https://sukhamburg.com/products/details/13MC-S1000_95CM-635-10-B07-M60-CS-7</u> from 4/26/2024

CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]

