

## 13MMC-S250-8+95CM-635-2-B08-M60-C-6

Laser Macro Focus Generator with rotationally symmetric beam profile



### FEATURES

Laser spot with rotationally symmetric, Gaussian beam profile and extended depth of focus.

- Spot diameter: 0.033 x 0.033 mm
- Wavelength: 635 nm
- Working distance: 234.7 mm
- Depth of focus: 2.76 mm

- Macro Focus Generator for extended depth of focus



## DESCRIPTION

The laser diode beam source type 13MMC-S250-8+95CM-635-2-B08-M60-C-6 produces a rotationally symmetric laser spot with extended depth of focus. The beam profile is rotationally symmetric and approx. Gaussian.

The laser type 13MMC-S250-8+95CM-635-2-B08-M60-C-6 produces a circular laser spot with extended depth of focus. The beam profile is approx. Gaussian.

The laser has integrated electronics [type C](#) for control of the laser output power. The output power can be controlled using the [modulation input ports \(TTL and analog\)](#), or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that the spot diameter increases proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

## TECHNICAL DATA

13MMC-S250-8+95CM-635-2-B08-M60-C-6

Series	13MMC	
Order Code	13MMC-S250-8+95CM-635-2-B08-M60-C-6	
Line profile	Gaussian Intensity Distribution	
Wavelength	635 +5/-5 nm	
Laser output power	2 mW	
Laser safety class	3R	
Focussing range	205-410 mm	
Working distance	234.7 mm	
Spot height	0.033 mm	
Spot width	0.033 mm	
Depth of focus	2.76 mm	
Diameter laser module	25/28 mm	
Module length	130.3 mm	
Installation length	395 mm	
Cable length	1.5 m	
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 ± 0.2 V	
Max. current consumption	0.25 A	
Working temperature	0 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	22 kOhm	22 kOhm
Max. modulation frequency	100 kHz	100 kHz
Modulation delay ON/OFF	1/0.5 µs	2/1 µs
Rise / Fall time	3/2 µs	3/2 µs

## ACCESSORIES

50HD-15	Hex key WS 1.5
9D-12	Screwdriver WS 1.2
PS051003E	Power Supply 5 V

## RELATED PRODUCTS

### LASER MODULES SERIES 13MC

- Micro Focus Generator
- **Rotationally symmetric**, Gaussian beam profile

### LASER MODULES SERIES LNC-13MMC

- Laser Macro Focus Generator
- **Rotationally symmetric** beam profile
- Extended depth of focus
- Low noise

### LASER MODULES SERIES 13MM

- Macro Focus Generator
- **Circular** beam profile
- Extended depth of focus

### LASER MODULES SERIES 5MM

- **Compact** Laser Macro Focus Generator
- **Circular** beam profile and
- Extended depth of focus

This is a printout of the page [https://sukhamburg.com/products/details/13MMC-S250-8\\_95CM-635-2-B08-M60-C-6](https://sukhamburg.com/products/details/13MMC-S250-8_95CM-635-2-B08-M60-C-6) from 5/2/2024

## CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

[info@sukhamburg.de](mailto:info@sukhamburg.de)

[www.sukhamburg.com](http://www.sukhamburg.com)

## LEGAL NOTICE

**Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.**

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)