

19.5AM25-L

Adapter for 60SMS Laser Beam Couplers Outer diameter Ø 25/28 mm



FEATURES

Adapter for 60SMS Laser Beam Couplers

- Outer diameter Ø 25/28 mm
- Fitting bore Ø 19.5 mm: accepts system mount Ø
 19.5 mm
- Long version e.g. to use with <u>ananorphic beam</u> <u>shaping optics</u>

TECHNICAL DATA

19.5AM25-L

Order Code		19.5AM25-L
Adapter	Fitting bore	Fitting bore
	Ø 19.5 mm	Ø 19.5 mm
Clear aperture		Ø 19.5 mm
Outer diameter		Ø 25/28 mm
Total length		20 mm
Material		Nickel silver
Weight		36 g

DOWNLOADS



930732000200.pdf (Dimensional drawing).



ACCESSORIES

50HD-15 Hex key WS 1.5

RELATED PRODUCTS

ADAPTERS FOR 60SMS, 60SMF, AND 60FC-A19.5

with system mount Ø 19.5 mm

OUSIVII, AND OUI C-AIS.

LASER BEAM
COUPLERS SERIES

60SMS

for coupling into single-mode and polarization-

maintaining fiber cables

ADAPTERS FOR FIBER

OPTICS

Adapters to use with fiber collimators and with the

multicube™ system.

This is a printout of the page https://sukhamburg.com/products/details/19 5AM25-L from 5/8/2024

CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany

Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]