### 25M-M35-26

**Micro Focus Optics** 



#### **FEATURES**

Micro focus optics used for focussing the collimated radiation exiting a fiber collimator.

- Attachment optics for fiber collimators type <u>60FC-L</u> or <u>60FC-T</u> with outer diameter Ø 32 mm
- Focal length f' = 35 mm
- AR Coating 420 700 nm
- Achromatic correction

## DESCRIPTION

The Micro Focus Optics type 25M-M35-26 is used to generate a small laser spot from the collimated radiation of a fiber collimator.

The <u>size of the spot</u> and its <u>Rayleigh range</u> is determined by the fiber properties and by the focal lengths of the fiber collimator and of the micro focus optics. For single-mode fibers the Gaussian intensity distribution and beam shape are maintained.

It is designed for the fiber collimators series <u>60FC-L</u> or <u>60FC-T</u> with an outer diameter Ø 32 mm.

#### Adjustment:

In order to change the working distance of the Micro Focus Optics the lens position of the adjacent collimator has to be readjusted.

#### Housing material:

As standard, the housing of the Micro Focus Optics is made of nickel silver. For amagnetic fiber collimators Schäfter+Kirchhoff offers Micro Focus Optics with housings made of titanium.

# **TECHNICAL DATA**

25M-M35-26

Series	25M
Order Code	25M-M35-26




## **DATA SHEET**

Focal length	35 mm
Working distance A	26.8 ± 0.1 mm
AR coating	26
Wavelength range	420 - 700 nm
Lens type	Doublet optics
Correction	Achromatic
Numerical aperture	0.34
Clear aperture	Ø 23.4 mm
Outer diameter	Ø 32 mm
Length B	12 mm
System mount	M27 x 0.5 mm
Front fitting	-
Housing material	Black anodized aluminum
Weight	

**RoHS compliant** 

Dimensions (for a complete dimensional drawing please refer to the downloads section)



## DOWNLOADS



980241290200.pdf (Dimensional drawing)



Coating-2601-02.pdf (Coating curve)



## **RELATED PRODUCTS**

MICRO FOCUS OPTICS SERIES 25M	for transforming a collimated beam into a micro focus spot
ATTACHMENT OPTICS SERIES 25	to attach in the front of collimators with M27x0.5 thread

This is a printout of the page https://sukhamburg.com/products/details/25M-M35-26 from 5/6/2024

### CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

# LEGAL NOTICE

#### Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]

