

Polarizer 48PM-AT-19.5AC-V

Polarizing beam splitting cube with attenuator, in adjustment mount



FEATURES

The polarization beam splitting cube 48PM-AT-19.5AC-V is used for polarization cleaning purposes in combination with PM fiber couplings. Only light with the correct polarization direction is transmitted. It has an integrated adjustable attenuator by means of a fine threaded screw. The polarization beam splitting has an adjustable mount. The 48PM-AT-19.5AC-V is designed to be integrated into the [multicube](#) system.

- Polarizing beam splitting cube
- Wavelength range 390 - 480 nm
- Extinction ratio 10,000 : 1
- Clear aperture 3.5 mm
- Integrated attenuator
- Broadband AR coating
- In adjustable mount
- System mount Ø 19.5 mm

TECHNICAL DATA

Polarizer 48PM-AT-19.5AC-V

Order code	48PM-AT-19.5AC-V
Type	Polarizing beam splitting cube
Wavelength range	390 - 480 nm
Extinction Ratio	10,000 : 1
AR Coating	390 - 480 nm
Clear aperture	3.5 mm
Rotation range	360°
Attenuator	Fine thread
	0.25 mm pitch

Connection	Flange mount
System mount	Ø 19.5 mm
Housing material	black anodized aluminum
Weight	

This is a printout of the page https://sukhamburg.com/products/details/48PM-AT-19_5AC-V from 5/3/2024

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)