

Polarization Beam Splitter 48PM-CC-RGB

Beam splitting cube, polarization dependent, in adjustment mount



FEATURES

The polarization beam splitter 48PM-CC-RGB is a polarization dependent cube beam splitters. It has an adjustable mount and is designed to be integrated into the [multicube](#) system.

- Beam splitting cube
- Polarization depending
- Wavelength range 400 - 700 nm
- Extinction ratio up to 200 : 1
- Clear aperture up to 3.5 mm
- Reflection angle 90°
- Broadband AR coating
- In adjustable mount
- Shipped with clamp collar

- RGB fiber optic components



TECHNICAL DATA

Polarization Beam Splitter 48PM-CC-RGB

Order code	48PM-CC-RGB
Type	Polarization beam splitter
Wavelength range	400 - 700 nm
Extinction Ratio	200 : 1
AR Coating	400 - 700 nm

Clear aperture	3.5 mm
Reflection angle	90°
Rotation range	360°
Tilt range	± 1.5°
Housing material	black anodized aluminum
Weight	

This is a printout of the page <https://sukhamburg.com/products/details/48PM-CC-RGB> from 5/8/2024

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)