

48PM-SXY-1-W

Polarizing beam splitting cube, in adjustment mount, laterally adjustable



FEATURES

The polarization beam splitting cube 48PM-SXY-1-W is used for polarization cleaning purposes in combination with PM fiber couplings. Only light with the correct polarization direction is transmitted. It has a system mount Ø 19.5 mm and it can be adjusted laterally in order to compensate for a beam offset. The polarizer can be rotated in its mount. The polarizer is designed to be integrated into the [multicube](#) system.

- Polarizing beam splitting cube
- Wavelength range 450 - 1000 nm
- Extinction ratio 10,000 : 1
- Clear aperture 3.5 mm
- Broadband AR coating
- Polarizer in adjustable mount
- System mount Ø 19.5 mm
- Laterally adjustable

TECHNICAL DATA

48PM-SXY-1-W

Order code	48PM-SXY-1-W
Type	Polarizing beam splitting cube
Wavelength range	450 - 1000 nm
Extinction Ratio	10,000 : 1
AR Coating	450 - 1000 nm
Clear aperture	3.5 mm
Laterally adjustable	± 0.8 mm
Rotation range	360°
Connection	Flange mount

System mount	Ø 19.5 mm
Housing material	black anodized aluminum
Weight	

This is a printout of the page <https://sukhamburg.com/products/details/48PM-SXY-1-W> from 4/30/2024

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)