


51nano-S-445-17-G02-P-12-4-28-0-150

Fiber-coupled low coherence laser source with polarization-maintaining fiber cable



FEATURES

The Laser Diode Beam Source of type 51nano-S-445-17-G02-P-12-4-28-0-150 has a reduced power noise, a reduced coherence length and a low speckle contrast.

- Reduced power noise: typ. < 0.06 % of P_0 (RMS, Bandwidth < 1 MHz)
- Reduced coherence length: coherence length \approx 300 μm
- Reduced speckle contrast
- Wavelength: 445 nm
- Laser output power: 17 mW
- Polarization-maintaining fiber cable
- FC APC connector (8°-polish) with end cap
- Modulation analog and TTL
- With interlock and key switch (conform to EN 60825-1)

Alternative: Laser Diode Beam Source 51nano-N (OEM version w/o key switch and w/o interlock)

DESCRIPTION

The fiber-coupled Laser Diode Beam Source of type 51nano-S-445-17-G02-P-12-4-28-0-150 has a reduced power noise (typ. < 0.06 % of P_0 (RMS, Bandwidth < 1 MHz)), reduced coherence length (\approx 300 μm) and a lowered speckle contrast.

Electrical features

The output power is adjustable using a potentiometer or using the two modulation inputs for analog and TTL.

Fiber cable

The source is fiber-coupled to a polarization-maintaining fiber cable (standard, polarization extinction ratio \geq 21 dB). As a result the beam profile is rotationally symmetric with Gaussian intensity distribution. The fiber cable is equipped with an FC APC type connector (8°-polish) and an end cap to prevent fiber damage. The fiber cable has a strain-relief and a protective sleeving (\varnothing 3 mm). Standard cable length is 150 cm.

Options:


- Single-mode fiber
- Multiple fiber output cables (51nanoC, single-mode only)
- Other connector types including FC PC, DIN or AVIO, or E2000
- Other fiber cable lengths
- Incorporated vacuum feed-through

Laser safety

The laser safety is conform to IEC 825 / EN 60825-1.

- Interlock chain for the remote deactivation of the laser
- Laser power-up is only possible using the key switch
- LED status indicator for "Laser ON"
- For a quick start the laser is shipped with a interlock connector type [BC0106F-iLCK](#)

An OEM version is available as type [51nano-N](#) without key switch or interlock which is not conform to EN 60825-1.




TECHNICAL DATA

51nano-S-445-17-G02-P-12-4-28-0-150

Order Code	51nano-S-445-17-G02-P-12-4-28-0-150
Will replace	51nanoL-S-445-17-G02-P-12-4-28-0-150
Series	51nano-S (PM)
Laser class	3B
Center wavelength	445 ± 15 nm
Bandwidth	0.7 - 4 nm
Output power	typ. 17 mW
Power adjustment	< 1 - 100 %
Power noise	typ. < 0.06 % of P ₀ (RMS, BW < 1 MHz)
Coherence length	≈ 300 μm

Fiber cable	polarization-maintaining	
Fiber type	PMC-E-460Si	
Nominal fiber NA	0.09	
Effective fiber NA _e ²	0.063 ± 10 % (1/e ²)	
Mode field diameter MFD	4.5 μm ± 10 % (1/e ²)	
PER	≥ 21 dB	
Fiber cable length	1.5 ± 0.05 m (standard)	
Fiber cable type	Ø 3 mm with Kevlar strain-relief	
Fiber connector type	FC APC with end cap (standard)	
Power stability	max. 12 % power variation between 15°C and 35°C	
Electronics type	HP	
Electr. cable length	1.5 ± 0.1 m (standard)	
Connector type	4 pin (male, Lumberg SV40)	
Supply voltage	12.0 ± 0.5 V	
Max. current consumption*	260 mA	
Modulation input connector	6 pin (male, Lumberg SV60)	
Modulation inputs	Analog	TTL
Max. input voltage	6.5 V	6.5 V
Voltage for P _{min} / P _O	0 V / 2.5 V	< 0.8 V / > 2.4 V
Input impedance	9 kOhm	9 kOhm
Max. modulation frequency	1 Hz	300 kHz
Modulation delay ON/OFF*	< 2.0/0.5 ms	< 0.5/0.2 μs
Rise / fall time*	0.5/0.5 s	0.8/0.3 μs
* Typical value. Depends on laser diode.		
Operating temperature	15 - 35°C ± 0.5°C	
Warm-up time	approx. 10 min	
Air humidity	max. 90 % non-condensing	
Weight	530 g	
Dimensions	50 x 58 x 166 mm	
Protection Class	IP30	

Dimensions (for a complete dimensional drawing please refer to the downloads section)



TECHNOTES

- [Fiber-coupled low noise beam source](#)
[Comparison of a low noise laser source to a conventional laser source](#)
- [51nano: Electronics Type HP](#)
[Electronic features for electronics type HP](#)

DOWNLOADS



[000829001100.pdf \(Dimensional drawing\).](#)



[Conformity_51nano_2023_E_web.PDF \(CE certificate\).](#)

ACCESSORIES

PS120516E

Power Supply 12 V

BC0106F-ILCK

Interlock connector

**FIBER COLLIMATORS
SINGLE-MODE/PM**

Fiber Collimators for collimating light exiting a single-mode or polarization-maintaining fiber cable

RELATED PRODUCTS

51NANO-S (SINGLE-MODE)

Fiber-coupled low coherence laser source with single-mode fiber cable

**51NANO-N
(POLARIZATION-
MAINTAINING, OEM)**

Fiber-coupled low coherence laser source with
polarization-maintaining fiber cable (OEM version)

**51NANOFI-S WITH
FARADAY ISOLATOR
(PM)**

Fiber-coupled low coherence laser source with
polarization-maintaining fiber cable

This is a printout of the page <https://sukhamburg.com/products/details/51nano-S-445-17-G02-P-12-4-28-0-150> from 5/6/2024

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)