5LM15-S000+25CM-785-90-Q06-A8-S-6


Compact Micro Line Generator with a fan angle



FEATURES

Compact laser line with a fan angle and Gaussian intensity distribution.

- Line length: 266 mm
- Line width: 470 μm
- Wavelength: 785 nm
- Working distance: 1000 mm
- Micro Line Generator for small laser line widths and high power density in the focal plane



DESCRIPTION

The laser diode beam source type 5LM15-S000+25CM-785-90-Q06-A8-S-6 has a fan angle of 15° .

The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 3 %. The line width is constant along the laser line. Across the laser line the intensity distribution is Gaussian.

The laser has integrated electronics <u>type S</u> for control of the laser output power. The output power can be controlled using the <u>modulation input ports (TTL and analog)</u> or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance.



A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

5LM15-S000+25CM-785-90-Q06-A8-S-6

Series		5LM
Order Code	5LM15-S000+25CM-785-90-Q06-A8-S-6	
Line profile	Gaussian Intensity Distribution	
Line type	Laser Micro Line	
Wavelength	785 +10/-10 nm	
Laser output power	90 mW	
ser safety class 38		
Fan angle α	15 deg	
ocussing range 425-inf mn		
Working distance 1000 mm		
Line length	266 mm	
Line width	0.47 mm	
Rayleigh range	441 mm	
Edge intensity	3%	
Diameter laser module	12 mm	
Module length	60.7 mm	
Installation length	1090.7 mm	
Cable length	1.5 m	
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 ± 0.25 V	
Max. current consumption	0.25 A	
Working temperature	0 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	22 kOhm	22 kOhm
Max. modulation frequency	50 kHz	1000 kHz
Modulation delay ON/OFF	4/0.5 μs	0.05/0.05 μs
Rise / Fall time	5/4 µs	0.1/0.02 μs



DOWNLOADS



921120000625.pdf

ACCESSORIES

60EX-4	Eccentric key with a stroke of \pm 0.5 mm.
60EX-4-L	Alternative eccentric key with long handle with a stroke of \pm 0.5 mm.
9D-12	Screwdriver WS 1.2
PS051003E	Power Supply 5 V

RELATED PRODUCTS

LASER MODULES SERIES 5LMM+25CM	 Compact Micro Line, small fan angle Gaussian intensity distribution Extended depth of focus
LASER MODULES SERIES LNC-5LM	 Micro Line, small fan angle Gaussian intensity distribution Low noise
LASER MODULES SERIES 13LR	 Micro Line Generator, fan angle Uniform intensity distribution
LASER MODULES SERIES 13LN	 Micro Line, small fan angle Uniform intensity distribution Thin lines
LASER MODULES SERIES 5LP+25CM	 Compact Micro Line, large fan angle Gaussian intensity distribution
LASER MODULES SERIES 5LM	 Micro Line, small fan angle Gaussian intensity distribution
LASER MODULES SERIES 5LP	 Micro Line, large fan angle Gaussian intensity distribution

Schäfter+Kirchhoff

DATA SHEET

This is a printout of the page <u>https://sukhamburg.com/products/details/5LM15-S000_25CM-785-90-Q06-A8-S-6</u> from 5/3/2024

CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]

