5LM15-S150+55CM-520-56-O11-A7.5-PS-7

Micro Line Generator with a fan angle



FEATURES

Laser line with a fan angle and Gaussian intensity distribution.

- Line length: 39.7 mm
- Line width: 72 µm
- Wavelength: 520 nm
- Working distance: 143 mm

- Micro Line Generator for small laser line widths and high power density in the focal plane
- With RS232 interface



DESCRIPTION

The laser diode beam source type 5LM15-S150+55CM-520-56-O11-A7.5-PS-7 has a fan angle of 15°.

The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 18 %. The line width is constant along the laser line. Across the laser line the intensity distribution is Gaussian.

The laser has integrated electronics type PS with micro-controller for control of the laser output power and serial interface (RS232). The output power can be controlled using the modulation input ports (TTL and analog) or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance.

A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

5LM15-S150+55CM-520-56-O11-A7.5-PS-7

Series		5LM
Order Code		5LM15-S150+55CM-520-56-O11-A7.5-PS-7
Line profile		Gaussian Intensity Distribution
Line type		Laser Micro Line
Wavelength		520 +10/-5 nm
Laser output power		56 mW
Laser safety class		3B
Fan angle α		15 deg
Focussing range		120-255 mm
Working distance		143 mm
Line length		39.7 mm
Line width		0.072 mm
Rayleigh range		15.7 mm
Edge intensity		18 %
Diameter laser module		25/28 mm
Module length		77.3 mm
Installation length		250.3 mm
Cable length		1.5 m
Connector type		Lumberg SV70 IEC 61076-2-106
Supply voltage		5 ± 0.2 V
Max. current consumption		0.5 A
Working temperature		15 - 40 °C
Modulation inputs	Analog	TTL
Input resistance	9 kOhm	9 kOhm
Max. modulation frequency	0.001 kHz	250 kHz
Modulation delay ON/OFF	3000/3000 µs	0.6/0.2 µs
Rise / Fall time	200000/200000 µs	0.2/0.2 µs
Interface		RS232

ACCESSORIES

50HD-15	Hex key WS 1.5
9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile
PS051007E	Power Supply 5 V for laser modules with RS232 interface

RELATED PRODUCTS

LASER MODULES SERIES 5LMM	▪ Macro Line, **small** fan angle ▪ Gaussian intensity distribution ▪ Extended depth of focus
LASER MODULES SERIES LNC-5LM	▪ Micro Line, **small** fan angle ▪ Gaussian intensity distribution ▪ Low noise
LASER MODULES SERIES 13LR	▪ Micro Line Generator, fan angle ▪ Uniform intensity distribution
LASER MODULES SERIES 13LN	▪ Micro Line, **small** fan angle ▪ Uniform intensity distribution ▪ Thin lines
LASER MODULES SERIES 5LP+25CM	▪ **Compact** Micro Line, **large** fan angle ▪ Gaussian intensity distribution
LASER MODULES SERIES 5LM+25CM	▪ **Compact** Micro Line, **small** fan angle ▪ Gaussian intensity distribution
LASER MODULES SERIES 5LP	▪ Micro Line, **large** fan angle ▪ Gaussian intensity distribution

This is a printout of the page https://sukhamburg.com/products/details/5LM15-S150_55CM-520-56-O11-A7_5-PS-7 from 3/28/2024

CONTACT

For more information please contact:
Schäfter + Kirchhoff GmbH
Kieler Str. 212
22525 Hamburg
Germany
Tel: +49 40 85 39 97-0
Fax: +49 40 85 39 97-79

info@sukhamburg.de
www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]