

## 5LM15-S50+25CM-785-90-Q06-A8-S-6

Compact Micro Line Generator with a fan angle



### FEATURES

Compact laser line with a fan angle and Gaussian intensity distribution.

- Line length: 11.9 mm
- Line width: 23  $\mu\text{m}$
- Wavelength: 785 nm
- Working distance: 42 mm

- Micro Line Generator for small laser line widths and high power density in the focal plane



## DESCRIPTION

The laser diode beam source type 5LM15-S50+25CM-785-90-Q06-A8-S-6 has a fan angle of 15°.

The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 3 %. The line width is constant along the laser line. Across the laser line the intensity distribution is Gaussian.

The laser has integrated electronics [type S](#) for control of the laser output power. The output power can be controlled using the [modulation input ports \(TTL and analog\)](#), or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance.

A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

## TECHNICAL DATA

5LM15-S50+25CM-785-90-Q06-A8-S-6

<b>Series</b>	5LM	
<b>Order Code</b>	5LM15-S50+25CM-785-90-Q06-A8-S-6	
<b>Line profile</b>	Gaussian Intensity Distribution	
<b>Line type</b>	Laser Micro Line	
<b>Wavelength</b>	785 +10/-10 nm	
<b>Laser output power</b>	90 mW	
<b>Laser safety class</b>	3B	
<b>Fan angle <math>\alpha</math></b>	15 deg	
<b>Focussing range</b>	30-65 mm	
<b>Working distance</b>	42 mm	
<b>Line length</b>	11.9 mm	
<b>Line width</b>	0.023 mm	
<b>Rayleigh range</b>	1.1 mm	
<b>Edge intensity</b>	3 %	
<b>Diameter laser module</b>	12 mm	
<b>Module length</b>	64.9 mm	
<b>Installation length</b>	136.9 mm	
<b>Cable length</b>	1.5 m	
<b>Connector type</b>	Lumberg SV50 IEC 61076-2-106	
<b>Supply voltage</b>	5 ± 0.25 V	
<b>Max. current consumption</b>	0.25 A	
<b>Working temperature</b>	0 - 40 °C	
<b>Modulation inputs</b>	Analog	TTL
<b>Input resistance</b>	22 kOhm	22 kOhm
<b>Max. modulation frequency</b>	50 kHz	1000 kHz
<b>Modulation delay ON/OFF</b>	4/0.5 $\mu$ s	0.05/0.05 $\mu$ s
<b>Rise / Fall time</b>	5/4 $\mu$ s	0.1/0.02 $\mu$ s

## DOWNLOADS



[921120000624.pdf](#)

## ACCESSORIES

60EX-4	Eccentric key with a stroke of $\pm 0.5$ mm.
60EX-4-L	Alternative eccentric key with long handle with a stroke of $\pm 0.5$ mm.
9D-12	Screwdriver WS 1.2
PS051003E	Power Supply 5 V

## RELATED PRODUCTS

### LASER MODULES SERIES 5LMM+25CM

- **Compact** Micro Line, **small** fan angle
- Gaussian intensity distribution
- Extended depth of focus

### LASER MODULES SERIES LNC-5LM

- Micro Line, **small** fan angle
- Gaussian intensity distribution
- Low noise

### LASER MODULES SERIES 13LR

- Micro Line Generator, fan angle
- Uniform intensity distribution

### LASER MODULES SERIES 13LN

- Micro Line, **small** fan angle
- Uniform intensity distribution
- Thin lines

### LASER MODULES SERIES 5LP+25CM

- **Compact** Micro Line, **large** fan angle
- Gaussian intensity distribution

### LASER MODULES SERIES 5LM

- Micro Line, **small** fan angle
- Gaussian intensity distribution

### LASER MODULES SERIES 5LP

- Micro Line, **large** fan angle
- Gaussian intensity distribution

This is a printout of the page [https://sukhamburg.com/products/details/5LM15-S50\\_25CM-785-90-Q06-A8-S-6](https://sukhamburg.com/products/details/5LM15-S50_25CM-785-90-Q06-A8-S-6) from 6/1/2023

## CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

[info@sukhamburg.de](mailto:info@sukhamburg.de)

[www.sukhamburg.com](http://www.sukhamburg.com)

## LEGAL NOTICE

**Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.**

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)