5LM15-S50+55CM-639-18-H18-A8-C-6


Micro Line Generator with a fan angle



FEATURES

Laser line with a fan angle and Gaussian intensity distribution.

- Line length: 11.9 mm
- Line width: 21 μm
- Wavelength: 639 nm
- Working distance: 42 mm
- Micro Line Generator for small laser line widths and high power density in the focal plane



DESCRIPTION

The laser diode beam source type 5LM15-S50+55CM-639-18-H18-A8-C-6 has a fan angle of 15°.

The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 38 %. The line width is constant along the laser line. Across the laser line the intensity distribution is Gaussian.

The laser has integrated electronics <u>type C</u> for control of the laser output power. The output power can be controlled using the <u>modulation input ports (TTL and analog)</u> or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance.



A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

5LM15-S50+55CM-639-18-H18-A8-C-6

Series		5LM
Order Code	5LM15-S50+55CM-639-18-H18-A8-C-6	
Line profile	Gaussian Intensity Distribution	
Line type	Laser Micro Line	
Wavelength	639 +10/-10 nm	
Laser output power	18 mW	
Laser safety class	3В	
Fan angle α	15 deg	
Focussing range	30-65 mm	
Vorking distance42 mm		
Line length	11.9 mm	
Line width	0.021 mm	
Rayleigh range	1.14 mm	
Edge intensity	38 %	
Diameter laser module	25/28 mm	
Module length	77.3 mm	
Installation length	149.3 mm	
cable length 1.5 m		1.5 m
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 ± 0.2 V	
Max. current consumption	0.25 A	
Working temperature	0 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	22 kOhm	22 kOhm
Max. modulation frequency	100 kHz	100 kHz
Modulation delay ON/OFF	1/0.5 µs	2/1 μs
Rise / Fall time	3/2 µs	3/2 µs



ACCESSORIES

50HD-15	Hex key WS 1.5
9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile
PS051003E	Power Supply 5 V

RELATED PRODUCTS

LASER MODULES SERIES 5LMM	 Macro Line, small fan angle Gaussian intensity distribution Extended depth of focus
LASER MODULES SERIES LNC-5LM	 Micro Line, small fan angle Gaussian intensity distribution Low noise
LASER MODULES SERIES 13LR	 Micro Line Generator, fan angle Uniform intensity distribution
LASER MODULES SERIES 13LN	 Micro Line, small fan angle Uniform intensity distribution Thin lines
LASER MODULES SERIES 5LP+25CM	 Compact Micro Line, large fan angle Gaussian intensity distribution
LASER MODULES SERIES 5LM+25CM	 Compact Micro Line, small fan angle Gaussian intensity distribution
LASER MODULES SERIES 5LP	 Micro Line, large fan angle Gaussian intensity distribution



DATA SHEET

This is a printout of the page <u>https://sukhamburg.com/products/details/5LM15-S50_55CM-639-18-H18-A8-C-6</u> from 5/2/2024

CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]

