

5LM8-S325+55CM-405-13-Y07-A7.5-C-6

Micro Line Generator with a fan angle



FEATURES

Laser line with a fan angle and Gaussian intensity distribution.

- Line length: 47.5 mm
- Line width: 89 μm
- Wavelength: 405 nm
- Working distance: 313 mm

-
- Micro Line Generator for small laser line widths and high power density in the focal plane



DESCRIPTION

The laser diode beam source type 5LM8-S325+55CM-405-13-Y07-A7.5-C-6 has a fan angle of 8°.

The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 9 %. The line width is constant along the laser line. Across the laser line the intensity distribution is Gaussian.

The laser has integrated electronics [type C](#) for control of the laser output power. The output power can be controlled using the [modulation input ports \(TTL and analog\)](#), or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance.

A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

5LM8-S325+55CM-405-13-Y07-A7.5-C-6

Series	5LM	
Order Code	5LM8-S325+55CM-405-13-Y07-A7.5-C-6	
Line profile	Gaussian Intensity Distribution	
Line type	Laser Micro Line	
Wavelength	405 +5/-5 nm	
Laser output power	13 mW	
Laser safety class	3B	
Fan angle α	8 deg	
Focussing range	255-425 mm	
Working distance	313 mm	
Line length	47.5 mm	
Line width	0.089 mm	
Rayleigh range	30.7 mm	
Edge intensity	9 %	
Diameter laser module	25/28 mm	
Module length	77.3 mm	
Installation length	420.3 mm	
Cable length	1.5 m	
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 \pm 0.2 V	
Max. current consumption	0.5 A	
Working temperature	0 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	22 kOhm	22 kOhm
Max. modulation frequency	100 kHz	100 kHz
Modulation delay ON/OFF	1/0.5 μ s	2/1 μ s
Rise / Fall time	3/2 μ s	3/2 μ s

ACCESSORIES

50HD-15	Hex key WS 1.5
9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile
PS051003E	Power Supply 5 V

RELATED PRODUCTS

LASER MODULES SERIES 5LMM	<ul style="list-style-type: none">▪ Macro Line, small fan angle▪ Gaussian intensity distribution▪ Extended depth of focus
LASER MODULES SERIES LNC-5LM	<ul style="list-style-type: none">▪ Micro Line, small fan angle▪ Gaussian intensity distribution▪ Low noise
LASER MODULES SERIES 13LR	<ul style="list-style-type: none">▪ Micro Line Generator, fan angle▪ Uniform intensity distribution
LASER MODULES SERIES 13LN	<ul style="list-style-type: none">▪ Micro Line, small fan angle▪ Uniform intensity distribution▪ Thin lines
LASER MODULES SERIES 5LP+25CM	<ul style="list-style-type: none">▪ Compact Micro Line, large fan angle▪ Gaussian intensity distribution
LASER MODULES SERIES 5LM+25CM	<ul style="list-style-type: none">▪ Compact Micro Line, small fan angle▪ Gaussian intensity distribution
LASER MODULES SERIES 5LP	<ul style="list-style-type: none">▪ Micro Line, large fan angle▪ Gaussian intensity distribution

This is a printout of the page https://sukhamburg.com/products/details/5LM8-S325_55CM-405-13-Y07-A7_5-C-6 from 4/19/2024

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)