

## 5LM8-S88+55CM-685-36-H13-A8-C-6

Micro Line Generator with a fan angle



#### **FEATURES**

Laser line with a fan angle and Gaussian intensity distribution.

Line length: 12 mm
Line width: 34 μm
Wavelength: 685 nm
Working distance: 78 mm

 Micro Line Generator for small laser line widths and high power density in the focal plane



#### DESCRIPTION

The laser diode beam source type 5LM8-S88+55CM-685-36-H13-A8-C-6 has a fan angle of 8°.

The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 19 %. The line width is constant along the laser line. Across the laser line the intensity distribution is Gaussian.

The laser has integrated electronics  $\underline{type\ C}$  for control of the laser output power. The output power can be controlled using the  $\underline{modulation\ input\ ports\ (TTL\ and\ analog)}$  or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance.



A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

# **TECHNICAL DATA**

5LM8-S88+55CM-685-36-H13-A8-C-6

Series		5LM
Order Code	5LM8-S88+55CM-685-36-H13-A8-C-6	
Line profile	Gaussian Intensity Distribution	
Line type	Laser Micro Line	
Wavelength	685 +10/-10 nm	
Laser output power	36 mW	
Laser safety class	3B	
Fan angle $\alpha$	8 deg	
Focussing range	65-120 mm	
Working distance	78 mm	
Line length	12 mm	
Line width	0.034 mm	
Rayleigh range	2.68 mm	
Edge intensity	19 %	
Diameter laser module	25/28 mm	
Module length	77.3 mm	
Installation length	185.3 mm	
Cable length	1.5 m	
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 ± 0.2 V	
Max. current consumption	0.25 A	
Working temperature	0 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	22 kOhm	22 kOhm
Max. modulation frequency	100 kHz	100 kHz
Modulation delay ON/OFF	1/0.5 µs	2/1 μs
Rise / Fall time	3/2 μs	3/2 µs



### **ACCESSORIES**

50HD-15 Hex key WS 1.5

9D-12 Screwdriver WS 1.2

13MK-25-36-10-F Mounting Console with flat base plate

13MK-25-36-10-M Mounting Console with base plate with dovetail

profile

Power Supply 5 V PS051003E

#### RELATED PRODUCTS

**LASER MODULES** • Macro Line, small fan angle **SERIES 5LMM** 

Gaussian intensity distribution

Extended depth of focus

LASER MODULES Micro Line, small fan angle **SERIES LNC-5LM** 

Gaussian intensity distribution

Low noise

Micro Line Generator, fan angle LASER MODULES

**SERIES 13LR** Uniform intensity distribution

**LASER MODULES** Micro Line, small fan angle **SERIES 13LN** 

Uniform intensity distribution

Thin lines

Compact Micro Line, large fan angle LASER MODULES

**SERIES 5LP+25CM** Gaussian intensity distribution

**LASER MODULES** Compact Micro Line, small fan angle

**SERIES 5LM+25CM** Gaussian intensity distribution

**LASER MODULES** Micro Line, large fan angle

**SERIES 5LP** Gaussian intensity distribution



This is a printout of the page <a href="https://sukhamburg.com/products/details/5LM8-S88">https://sukhamburg.com/products/details/5LM8-S88</a> 55CM-685-36-H13-A8-C-6 from 5/2/2024

### CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany

Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

### **LEGAL NOTICE**

#### Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]