

5LMM15-S325-1+55CM-405-60-X15-A7.5-P-6

Macro Line Generator with a fan angle




FEATURES

Laser line with a fan angle, Gaussian intensity distribution and extended depth of focus.

- Line length: 86.9 mm
- Line width: 191 μm
- Wavelength: 405 nm
- Working distance: 308 mm
- Depth of focus: 191 mm

-
- Macro Line Generator for extended depth of focus



DESCRIPTION

The laser diode beam source type 5LMM15-S325-1+55CM-405-60-X15-A7.5-P-6 has a fan angle of 15° and an extended depth of focus.

The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 10 %. The line width is constant along the laser line. Across the laser line the intensity distribution is approx. Gaussian.

The laser has integrated electronics [type P](#) with micro-controller for control of the laser output power. The output power can be controlled using the [modulation input ports \(TTL and analog\)](#), or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

5LMM15-S325-1+55CM-405-60-X15-A7.5-P-6

Series	5LMM	
Order Code	5LMM15-S325-1+55CM-405-60-X15-A7.5-P-6	
Line profile	Gaussian Intensity Distribution	
Line type	Laser Macro Line	
Wavelength	405 +5/-5 nm	
Laser output power	60 mW	
Laser safety class	3B	
Fan angle α	15 deg	
Focussing range	250-450 mm	
Working distance	308 mm	
Line length	86.9 mm	
Line width	0.191 mm	
Depth of focus	191 mm	
Edge intensity	10 %	
Diameter laser module	25/28 mm	
Module length	78.5 mm	
Installation length	416.5 mm	
Cable length	1.5 m	
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 \pm 0.2 V	
Max. current consumption	0.5 A	
Working temperature	15 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	9 kOhm	9 kOhm
Max. modulation frequency	0.01 kHz	250 kHz
Modulation delay ON/OFF	3000/3000 μ s	0.5/0.2 μ s
Rise / Fall time	40000/40000 μ s	0.5/0.5 μ s

ACCESSORIES

50HD-15

Hex key WS 1.5

9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile
PS051003E	Power Supply 5 V

RELATED PRODUCTS

LASER MODULES SERIES 5LM

- Micro Line, **small** fan angle
- Gaussian intensity distribution

LASER MODULES SERIES LNC-5LMM

- Macro Line, **small** fan angle
- Gaussian intensity distribution
- Extended depth of focus
- Low Noise

LASER MODULES SERIES 13LRM

- Macro Line Generator, fan angle
- Uniform intensity distribution
- Extended depth of focus

LASER MODULES SERIES 13LNM

- Micro Line Generator, **small** fan angle
- Uniform intensity distribution
- Extended depth of focus

LASER MODULES SERIES 5LPM+25CM

- **Compact** Macro Line, **large** fan angle
- Gaussian intensity distribution
- Extended depth of focus

LASER MODULES SERIES 5LMM+25CM

- **Compact** Micro Line, **small** fan angle
- Gaussian intensity distribution
- Extended depth of focus

LASER MODULES SERIES 5LPM

- Macro Line, **large** fan angle
- Gaussian intensity distribution
- Extended depth of focus

This is a printout of the page https://sukhamburg.com/products/details/5LMM15-S325-1_55CM-405-60-X15-A7_5-P-6 from 6/4/2023

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)