

5LMM8-S325-1+25CM-639-13-H18-A8-S-6

Compact Macro Line Generator with a fan angle




FEATURES

Compact laser line with a fan angle, Gaussian intensity distribution and extended depth of focus.

- Line length: 47.5 mm
- Line width: 302 μm
- Wavelength: 639 nm
- Working distance: 308 mm
- Depth of focus: 301 mm

-
- Macro Line Generator for extended depth of focus



DESCRIPTION

The laser diode beam source type 5LMM8-S325-1+25CM-639-13-H18-A8-S-6 has a fan angle of 8° and an extended depth of focus.

The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 40 %. The line width is constant along the laser line. Across the laser line the intensity distribution is approx. Gaussian.

The laser has integrated electronics [type S](#) for control of the laser output power. The output power can be controlled using the [modulation input ports \(TTL and analog\)](#), or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

5LMM8-S325-1+25CM-639-13-H18-A8-S-6

Series	5LMM	
Order Code	5LMM8-S325-1+25CM-639-13-H18-A8-S-6	
Line profile	Gaussian Intensity Distribution	
Line type	Laser Macro Line	
Wavelength	639 +10/-10 nm	
Laser output power	13 mW	
Laser safety class	3B	
Fan angle α	8 deg	
Focussing range	250-450 mm	
Working distance	308 mm	
Line length	47.5 mm	
Line width	0.302 mm	
Depth of focus	301 mm	
Edge intensity	40 %	
Diameter laser module	12 mm	
Module length	66.1 mm	
Installation length	404.1 mm	
Cable length	1.5 m	
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 \pm 0.25 V	
Max. current consumption	0.25 A	
Working temperature	0 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	22 kOhm	22 kOhm
Max. modulation frequency	50 kHz	1000 kHz
Modulation delay ON/OFF	4/0.5 μ s	0.05/0.05 μ s
Rise / Fall time	5/4 μ s	0.1/0.02 μ s

ACCESSORIES

60EX-4 Eccentric key with a stroke of \pm 0.5 mm.

60EX-4-L	Alternative eccentric key with long handle with a stroke of ± 0.5 mm.
9D-12	Screwdriver WS 1.2
PS051003E	Power Supply 5 V

RELATED PRODUCTS

LASER MODULES SERIES 5LMM+25CM

- **Compact** Micro Line, **small** fan angle
- Gaussian intensity distribution
- Extended depth of focus

LASER MODULES SERIES LNC-5LMM

- Macro Line, **small** fan angle
- Gaussian intensity distribution
- Extended depth of focus
- Low Noise

LASER MODULES SERIES 13LRM

- Macro Line Generator, fan angle
- Uniform intensity distribution
- Extended depth of focus

LASER MODULES SERIES 13LNM

- Micro Line Generator, **small** fan angle
- Uniform intensity distribution
- Extended depth of focus

LASER MODULES SERIES 5LPM+25CM

- **Compact** Macro Line, **large** fan angle
- Gaussian intensity distribution
- Extended depth of focus

LASER MODULES SERIES 5LMM

- Macro Line, **small** fan angle
- Gaussian intensity distribution
- Extended depth of focus

LASER MODULES SERIES 5LPM

- Macro Line, **large** fan angle
- Gaussian intensity distribution
- Extended depth of focus

This is a printout of the page https://sukhamburg.com/products/details/5LMM8-S325-1_25CM-639-13-H18-A8-S-6
from 6/4/2023

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)