5LMM8-S325-1+55CM-450-44-O06-A7.5-P-6


Macro Line Generator with a fan angle

FEATURES

Laser line with a fan angle, Gaussian intensity distribution and extended depth of focus.

- Line length: 47.5 mm
- Line width: 215 µm
- Wavelength: 450 nm
- Working distance: 308 mm
- Depth of focus: 212 mm

- Macro Line Generator for extended depth of focus



DESCRIPTION

The laser diode beam source type 5LMM8-S325-1+55CM-450-44-O06-A7.5-P-6 has a fan angle of 8° and an extended depth of focus.

The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 15 %. The line width is constant along the laser line. Across the laser line the intensity distribution is approx. Gaussian.

The laser has integrated electronics type P with micro-controller for control of the laser output power. The output power can be controlled using the modulation input ports (TTL and analog) or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

5LMM8-S325-1+55CM-450-44-O06-A7.5-P-6

Series	5LMM	
Order Code	5LMM8-S325-1+55CM-450-44-O06-A7.5-P-6	
Line profile	Gaussian Intensity Distribution	
Line type	Laser Macro Line	
Wavelength	450 +10/-10 nm	
Laser output power	44 mW	
Laser safety class	3B	
Fan angle α	8 deg	
Focussing range	250-450 mm	
Working distance	308 mm	
Line length	47.5 mm	
Line width	0.215 mm	
Depth of focus	212 mm	
Edge intensity	15 %	
Diameter laser module	25/28 mm	
Module length	78.5 mm	
Installation length	416.5 mm	
Cable length	1.5 m	
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 ± 0.2 V	
Max. current consumption	0.5 A	
Working temperature	15 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	9 kOhm	9 kOhm
Max. modulation frequency	0.01 kHz	250 kHz
Modulation delay ON/OFF	3000/3000 µs	0.5/0.2 µs
Rise / Fall time	40000/40000 µs	0.5/0.5 µs

ACCESSORIES

50HD-15	Hex key WS 1.5

9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile
PS051003E	Power Supply 5 V

RELATED PRODUCTS

LASER MODULES SERIES 5LM	▪ Micro Line, **small** fan angle ▪ Gaussian intensity distribution
LASER MODULES SERIES LNC-5LMM	▪ Macro Line, **small** fan angle ▪ Gaussian intensity distribution ▪ Extended depth of focus ▪ Low Noise
LASER MODULES SERIES 13LRM	▪ Macro Line Generator, fan angle ▪ Uniform intensity distribution ▪ Extended depth of focus
LASER MODULES SERIES 13LNM	▪ Micro Line Generator, **small** fan angle ▪ Uniform intensity distribution ▪ Extended depth of focus
LASER MODULES SERIES 5LPM+25CM	▪ **Compact** Macro Line, **large** fan angle ▪ Gaussian intensity distribution ▪ Extended depth of focus
LASER MODULES SERIES 5LMM+25CM	▪ **Compact** Micro Line, **small** fan angle ▪ Gaussian intensity distribution ▪ Extended depth of focus
LASER MODULES SERIES 5LPM	▪ Macro Line, **large** fan angle ▪ Gaussian intensity distribution ▪ Extended depth of focus

This is a printout of the page https://sukhamburg.com/products/details/5LMM8-S325-1_55CM-450-44-O06-A7_5-P-6 from 3/28/2024

CONTACT

For more information please contact:
Schäfter + Kirchhoff GmbH
Kieler Str. 212
22525 Hamburg
Germany
Tel: +49 40 85 39 97-0
Fax: +49 40 85 39 97-79

info@sukhamburg.de
www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]