

5LPM60-S88-1+55CM-639-13-H18-A8-CS-7

Macro Line Generator with a large fan angle




FEATURES

Laser line with a large fan angle, Gaussian intensity distribution and extended depth of focus.

- Line length: 92 mm
- Line width: 82 μm
- Wavelength: 639 nm
- Working distance: 77 mm
- Depth of focus: 22.1 mm

-
- Macro Line Generator for extended depth of focus
 - With RS232 interface



DESCRIPTION

The laser diode beam source type 5LPM60-S88-1+55CM-639-13-H18-A8-CS-7 has a fan angle of 62° and an extended depth of focus.

The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 38 %. The line width is constant along the laser line. Across the laser line the intensity distribution is approx. Gaussian.

The laser has integrated electronics [type CS](#) for control of the laser output power and serial interface (RS232). The output power can be controlled using the [modulation input ports \(TTL and analog\)](#) or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

5LPM60-S88-1+55CM-639-13-H18-A8-CS-7

Series	5LPM	
Order Code	5LPM60-S88-1+55CM-639-13-H18-A8-CS-7	
Line profile	Gaussian Intensity Distribution	
Line type	Laser Macro Line	
Wavelength	639 +10/-10 nm	
Laser output power	13 mW	
Laser safety class	3B	
Fan angle α	62 deg	
Focussing range	65-120 mm	
Working distance	77 mm	
Line length	92 mm	
Line width	0.082 mm	
Depth of focus	22.1 mm	
Edge intensity	38 %	
Diameter laser module	25/28 mm	
Module length	91.5 mm	
Installation length	198.5 mm	
Cable length	1.5 m	
Connector type	Lumberg SV70 IEC 61076-2-106	
Supply voltage	5 \pm 0.2 V	
Max. current consumption	0.25 A	
Working temperature	0 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	9 kOhm	9 kOhm
Max. modulation frequency	0.001 kHz	250 kHz
Modulation delay ON/OFF	3000/3000 μ s	0.5/0.2 μ s
Rise / Fall time	200000/200000 μ s	0.8/0.4 μ s

Interface

RS232

ACCESSORIES

50HD-15	Hex key WS 1.5
9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile
PS051007E	Power Supply 5 V for laser modules with RS232 interface

RELATED PRODUCTS

LASER MODULES SERIES 5LPM	<ul style="list-style-type: none">▪ Macro Line, large fan angle▪ Gaussian intensity distribution▪ Extended depth of focus
LASER MODULES SERIES LNC-5LPM	<ul style="list-style-type: none">▪ Macro Line, large fan angle▪ Gaussian intensity distribution▪ Extended depth of focus▪ Low noise
LASER MODULES SERIES 13LRM	<ul style="list-style-type: none">▪ Macro Line Generator, fan angle▪ Uniform intensity distribution▪ Extended depth of focus
LASER MODULES SERIES 13LNM	<ul style="list-style-type: none">▪ Micro Line Generator, small fan angle▪ Uniform intensity distribution▪ Extended depth of focus
LASER MODULES SERIES 5LMM+25CM	<ul style="list-style-type: none">▪ Compact Micro Line, small fan angle▪ Gaussian intensity distribution▪ Extended depth of focus
LASER MODULES SERIES 5LPM+25CM	<ul style="list-style-type: none">▪ Compact Macro Line, large fan angle▪ Gaussian intensity distribution▪ Extended depth of focus

This is a printout of the page https://sukhamburg.com/products/details/5LPM60-S88-1_55CM-639-13-H18-A8-CS-7
from 4/26/2024

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)