
#### 5LPM80-S325-1+25CM-405-10-Y07-A7.5-B-4


Compact Macro Line Generator with a large fan angle



#### FEATURES

Compact laser line with a large fan angle, Gaussian intensity distribution, and extended depth of focus.

- Line length: 565 mm
- Line width: 192 µm
- Wavelength: 405 nm
- Working distance: 312 mm
- Depth of focus: 191 mm
- Macro Line Generator for extended depth of focus



#### DESCRIPTION

The laser diode beam source type 5LPM80-S325-1+25CM-405-10-Y07-A7.5-B-4 has a fan angle of 84° and an extended depth of focus.

The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 9 %. The line width is constant along the laser line. Across the laser line the intensity distribution is approx. Gaussian.

The laser has integrated electronics <u>type B</u> for control of the laser output power. The output power can be controlled using the <u>modulation input port (TTL)</u> or manually using the potentiometer.



The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

### **TECHNICAL DATA**

5LPM80-S325-1+25CM-405-10-Y07-A7.5-B-4

Series	5LPM
Order Code	5LPM80-S325-1+25CM-405-10-Y07-A7.5-B-4
Line profile	Gaussian Intensity Distribution
Line type	Laser Macro Line
Wavelength	405 +5/-5 nm
Laser output power	10 mW
Laser safety class	3В
Fan angle α	84 deg
Focussing range	255-450 mm
Working distance	312 mm
Line length	565 mm
Line width	0.192 mm
Depth of focus	191 mm
Edge intensity	9 %
Diameter laser module	12 mm
Module length	79.1 mm
Installation length	421.1 mm
Cable length	1.5 m
Connector type	Lumberg SV40 IEC 61076-2-106
Supply voltage	12 ± 0.5 V
Max. current consumption	0.16 A
Working temperature	0 - 40 °C
Modulation inputs	TTL
Input resistance	110 kOhm
Max. modulation frequency	0.2 kHz
Modulation delay ON/OFF	500/500 μs
Rise / Fall time	10/20 μs



### ACCESSORIES

60EX-4	Eccentric key with a stroke of $\pm$ 0.5 mm.
60EX-4-L	Alternative eccentric key with long handle with a stroke of $\pm$ 0.5 mm.
9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile
PS120516E	Power Supply 12 V

## **RELATED PRODUCTS**

LASER MODULES SERIES 5LPM	<ul> <li>Macro Line, large fan angle</li> <li>Gaussian intensity distribution</li> <li>Extended depth of focus</li> </ul>
LASER MODULES SERIES LNC-5LPM	<ul> <li>Macro Line, large fan angle</li> <li>Gaussian intensity distribution</li> <li>Extended depth of focus</li> <li>Low noise</li> </ul>
LASER MODULES SERIES 13LRM	<ul> <li>Macro Line Generator, fan angle</li> <li>Uniform intensity distribution</li> <li>Extended depth of focus</li> </ul>
LASER MODULES SERIES 13LNM	<ul> <li>Micro Line Generator, small fan angle</li> <li>Uniform intensity distribution</li> <li>Extended depth of focus</li> </ul>
LASER MODULES SERIES 5LMM+25CM	<ul> <li>Compact Micro Line, small fan angle</li> <li>Gaussian intensity distribution</li> <li>Extended depth of focus</li> </ul>
LASER MODULES SERIES 5LPM+25CM	<ul> <li>Compact Macro Line, large fan angle</li> <li>Gaussian intensity distribution</li> <li>Extended depth of focus</li> </ul>





#### LASER MODULES SERIES 5LMM

- Macro Line, small fan angle
- Gaussian intensity distribution
  - Extended depth of focus

This is a printout of the page <u>https://sukhamburg.com/products/details/5LPM80-S325-1\_25CM-405-10-Y07-A7\_5-B-4</u> from 5/5/2024

### CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

# LEGAL NOTICE

#### Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]

