

5LPM80-S325-1+55CM-635-7-H10-A8-C-6

Macro Line Generator with a large fan angle



FEATURES

Laser line with a large fan angle, Gaussian intensity distribution and extended depth of focus.

- Line length: 565 mm
- Line width: 300 μm
- Wavelength: 635 nm
- Working distance: 312 mm
- Depth of focus: 299 mm

-
- Macro Line Generator for extended depth of focus



DESCRIPTION

The laser diode beam source type 5LPM80-S325-1+55CM-635-7-H10-A8-C-6 has a fan angle of 84° and an extended depth of focus.

The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 31 %. The line width is constant along the laser line. Across the laser line the intensity distribution is approx. Gaussian.

The laser has integrated electronics [type C](#) for control of the laser output power. The output power can be controlled using the [modulation input ports \(TTL and analog\)](#) or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

5LPM80-S325-1+55CM-635-7-H10-A8-C-6

Series	5LPM	
Order Code	5LPM80-S325-1+55CM-635-7-H10-A8-C-6	
Line profile	Gaussian Intensity Distribution	
Line type	Laser Macro Line	
Wavelength	635 +10/-10 nm	
Laser output power	7 mW	
Laser safety class	3B	
Fan angle α	84 deg	
Focussing range	255-450 mm	
Working distance	312 mm	
Line length	565 mm	
Line width	0.3 mm	
Depth of focus	299 mm	
Edge intensity	31 %	
Diameter laser module	25/28 mm	
Module length	91.5 mm	
Installation length	433.5 mm	
Cable length	1.5 m	
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 \pm 0.2 V	
Max. current consumption	0.25 A	
Working temperature	0 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	22 kOhm	22 kOhm
Max. modulation frequency	100 kHz	100 kHz
Modulation delay ON/OFF	1/0.5 μ s	2/1 μ s
Rise / Fall time	3/2 μ s	3/2 μ s

ACCESSORIES

50HD-15

Hex key WS 1.5

9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile
PS051003E	Power Supply 5 V

RELATED PRODUCTS

LASER MODULES SERIES 5LPM

- Macro Line, **large** fan angle
- Gaussian intensity distribution
- Extended depth of focus

LASER MODULES SERIES LNC-5LPM

- Macro Line, **large** fan angle
- Gaussian intensity distribution
- Extended depth of focus
- Low noise

LASER MODULES SERIES 13LRM

- Macro Line Generator, fan angle
- Uniform intensity distribution
- Extended depth of focus

LASER MODULES SERIES 13LNM

- Micro Line Generator, **small** fan angle
- Uniform intensity distribution
- Extended depth of focus

LASER MODULES SERIES 5LMM+25CM

- **Compact** Micro Line, **small** fan angle
- Gaussian intensity distribution
- Extended depth of focus

LASER MODULES SERIES 5LPM+25CM

- **Compact** Macro Line, **large** fan angle
- Gaussian intensity distribution
- Extended depth of focus

This is a printout of the page https://sukhamburg.com/products/details/5LPM80-S325-1_55CM-635-7-H10-A8-C-6
from 5/7/2024

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)