


## 5LT-100-1+25CM-635-10-H10-A8-S-6

Semi-telecentric compact Micro Line Generator



### FEATURES

Semi-telecentric compact laser line with constant line length of 4.8 mm.

- Line length: 4.8 mm
- Line width: 43  $\mu\text{m}$
- Wavelength: 635 nm
- Working distance: 96 mm

- Micro Line Generator for small laser line widths and high power density in the focal plane



## DESCRIPTION

The laser diode beam source type 5LT-100-1+25CM-635-10-H10-A8-S-6 produces a semi-telecentric laser line with 4.8 mm line length. The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 33 %. The line width is constant along the laser line. Across the laser line the intensity distribution is Gaussian.

The laser has integrated electronics [type S](#) for control of the laser output power. The output power can be controlled using the [modulation input ports \(TTL and analog\)](#), or manually using the potentiometer.

For this laser type the working distance is fixed. A fine-adjustment of the distance between laser and target is recommended for fine-focusing in order to achieve minimal line width.

## TECHNICAL DATA

5LT-100-1+25CM-635-10-H10-A8-S-6

Series	5LT	
Order Code	5LT-100-1+25CM-635-10-H10-A8-S-6	
Line profile	Gaussian Intensity Distribution	
Line type	Laser Micro Line	
Wavelength	635 +10/-10 nm	
Laser output power	10 mW	
Laser safety class	3B	
Focussing range	96-96 mm	
Working distance	96 mm	
Line length	4.8 mm	
Line width	0.043 mm	
Rayleigh range	4.51 mm	
Edge intensity	33 %	
Diameter laser module	12 mm	
Module length	60.7 mm	
Installation length	186.7 mm	
Cable length	1.5 m	
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 ± 0.25 V	
Max. current consumption	0.25 A	
Working temperature	0 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	22 kOhm	22 kOhm
Max. modulation frequency	50 kHz	1000 kHz
Modulation delay ON/OFF	4/0.5 µs	0.05/0.05 µs
Rise / Fall time	5/4 µs	0.1/0.02 µs

## DOWNLOADS

[921120000614.pdf](#)

## ACCESSORIES

9D-12	Screwdriver WS 1.2
PS051003E	Power Supply 5 V

## RELATED PRODUCTS

### LASER MODULES SERIES 5LTM-1+25CM

- **Compact** semi-telecentric Macro Line
- Gaussian intensity distribution
- Constant line length ca. **4.8 mm**
- Extended depth of focus

### LASER MODULES SERIES 13LT

- Semi-telecentric Micro Line
- Uniform intensity distribution
- Constant line length **15 mm**

### LASER MODULES SERIES 5LT-2+25CM

- **Compact** semi-telecentric Micro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**

### LASER MODULES SERIES 5LT-1

- Semi-telecentric Micro Line
- Gaussian intensity distribution
- Constant line length ca. **4.8 mm**

### LASER MODULES SERIES 5LT-2

- Semi-telecentric Micro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**

This is a printout of the page [https://sukhamburg.com/products/details/5LT-100-1\\_25CM-635-10-H10-A8-S-6](https://sukhamburg.com/products/details/5LT-100-1_25CM-635-10-H10-A8-S-6) from 5/4/2024

## CONTACT

For more information please contact:

**Schäfter + Kirchhoff GmbH**

**Kieler Str. 212**

**22525 Hamburg**

**Germany**

**Tel: +49 40 85 39 97-0**

**Fax: +49 40 85 39 97-79**

**[info@sukhamburg.de](mailto:info@sukhamburg.de)**

**[www.sukhamburg.com](http://www.sukhamburg.com)**

## LEGAL NOTICE

**Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.**

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)