

5LT-250-2+55CM-450-57-O06-A7.5-PS-7

Semi-telecentric Micro Line Generator



FEATURES

Semi-telecentric laser line with constant line length of 2.4 mm.

- Line length: 2.4 mm
- Line width: 32 μm
- Wavelength: 450 nm
- Working distance: 250 mm

- Micro Line Generator for small laser line widths and high power density in the focal plane
- With RS232 interface



DESCRIPTION

The laser diode beam source type 5LT-250-2+55CM-450-57-O06-A7.5-PS-7 produces a semi-telecentric laser line with 2.4 mm line length. In this case the line length is given on the 13.5%-level. The intensity profile is Gaussian in line direction and the line is truncated at 4.8 mm. The line width is constant along the laser line. Across the laser line the intensity distribution is Gaussian.

The laser has integrated electronics [type PS](#) with micro-controller for control of the laser output power and serial interface (RS232). The output power can be controlled using the [modulation input ports \(TTL and analog\)](#), or manually using the potentiometer.

For this laser type the working distance is fixed. A fine-adjustment of the distance between laser and target is recommended for fine-focusing in order to achieve minimal line width.

TECHNICAL DATA

5LT-250-2+55CM-450-57-O06-A7.5-PS-7

Series	5LT	
Order Code	5LT-250-2+55CM-450-57-O06-A7.5-PS-7	
Line profile	Gaussian Intensity Distribution	
Line type	Laser Micro Line	
Wavelength	450 +10/-10 nm	
Laser output power	57 mW	
Laser safety class	3B	
Focussing range	250-250 mm	
Working distance	250 mm	
Line length	2.4 mm	
Line width	0.032 mm	
Rayleigh range	3.54 mm	
Edge intensity	15 %	
Diameter laser module	25/28 mm	
Module length	73.1 mm	
Installation length	353.1 mm	
Cable length	1.5 m	
Connector type	Lumberg SV70 IEC 61076-2-106	
Supply voltage	5 ± 0.2 V	
Max. current consumption	0.5 A	
Working temperature	15 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	9 kOhm	9 kOhm
Max. modulation frequency	0.001 kHz	250 kHz
Modulation delay ON/OFF	3000/3000 µs	0.6/0.2 µs
Rise / Fall time	200000/200000 µs	0.2/0.2 µs
Interface	RS232	

DOWNLOADS



[930412000106.pdf](#)

ACCESSORIES

9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile
PS051007E	Power Supply 5 V for laser modules with RS232 interface

RELATED PRODUCTS

LASER MODULES SERIES 5LTM-2

- Semi-telecentric Macro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**
- Extended depth of focus

LASER MODULES SERIES LNC-5LTM-2

- Semi-telecentric Macro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**
- Extended depth of focus
- Low noise

LASER MODULES SERIES 13LT

- Semi-telecentric Micro Line
- Uniform intensity distribution
- Constant line length **15 mm**

LASER MODULES SERIES 5LT-1+25CM

- **Compact** semi-telecentric Micro Line
- Gaussian intensity distribution
- Constant line length ca. **4.8 mm**

LASER MODULES SERIES 5LT-1

- Semi-telecentric Micro Line
- Gaussian intensity distribution
- Constant line length ca. **4.8 mm**

**LASER MODULES
SERIES 5LT-2+25CM**

- **Compact** semi-telecentric Micro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**

This is a printout of the page https://sukhamburg.com/products/details/5LT-250-2_55CM-450-57-O06-A7_5-PS-7 from 5/8/2024

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)