

## 5LT-500-1+55CM-635-10-H10-A8-CS-7

Semi-telecentric Micro Line Generator




### FEATURES

Semi-telecentric laser line with constant line length of 4.8 mm.

- Line length: 4.8 mm
- Line width: 214  $\mu\text{m}$
- Wavelength: 635 nm
- Working distance: 491 mm

- 
- Micro Line Generator for small laser line widths and high power density in the focal plane
  - With RS232 interface



## DESCRIPTION

The laser diode beam source type 5LT-500-1+55CM-635-10-H10-A8-CS-7 produces a semi-telecentric laser line with 4.8 mm line length. The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 33 %. The line width is constant along the laser line. Across the laser line the intensity distribution is Gaussian.

The laser has integrated electronics [type CS](#) for control of the laser output power and serial interface (RS232). The output power can be controlled using the [modulation input ports \(TTL and analog\)](#), or manually using the potentiometer.

For this laser type the working distance is fixed. A fine-adjustment of the distance between laser and target is recommended for fine-focusing in order to achieve minimal line width.

## TECHNICAL DATA

5LT-500-1+55CM-635-10-H10-A8-CS-7

<b>Series</b>	5LT	
<b>Order Code</b>	5LT-500-1+55CM-635-10-H10-A8-CS-7	
<b>Line profile</b>	Gaussian Intensity Distribution	
<b>Line type</b>	Laser Micro Line	
<b>Wavelength</b>	635 +10/-10 nm	
<b>Laser output power</b>	10 mW	
<b>Laser safety class</b>	3B	
<b>Focussing range</b>	491-491 mm	
<b>Working distance</b>	491 mm	
<b>Line length</b>	4.8 mm	
<b>Line width</b>	0.214 mm	
<b>Rayleigh range</b>	113 mm	
<b>Edge intensity</b>	33 %	
<b>Diameter laser module</b>	25/28 mm	
<b>Module length</b>	73.1 mm	
<b>Installation length</b>	594.1 mm	
<b>Cable length</b>	1.5 m	
<b>Connector type</b>	Lumberg SV70 IEC 61076-2-106	
<b>Supply voltage</b>	5 ± 0.2 V	
<b>Max. current consumption</b>	0.25 A	
<b>Working temperature</b>	0 - 40 °C	
<b>Modulation inputs</b>	Analog	TTL
<b>Input resistance</b>	9 kOhm	9 kOhm
<b>Max. modulation frequency</b>	0.001 kHz	250 kHz
<b>Modulation delay ON/OFF</b>	3000/3000 µs	0.5/0.2 µs
<b>Rise / Fall time</b>	200000/200000 µs	0.8/0.4 µs
<b>Interface</b>	RS232	

## DOWNLOADS



[930412000106.pdf](#)

## ACCESSORIES

9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile
PS051007E	Power Supply 5 V for laser modules with RS232 interface

## RELATED PRODUCTS

### LASER MODULES SERIES 5LTM-1

- Semi-telecentric Macro Line
- Gaussian intensity distribution
- Constant line length ca. **4.8 mm**
- Extended depth of focus

### LASER MODULES SERIES LNC-5LTM-1

- Semi-telecentric Macro Line
- Gaussian intensity distribution
- Constant line length ca. **4.8 mm**
- Extended depth of focus
- Low noise

### LASER MODULES SERIES 13LT

- Semi-telecentric Micro Line
- Uniform intensity distribution
- Constant line length **15 mm**

### LASER MODULES SERIES 5LT-2+25CM

- **Compact** semi-telecentric Micro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**

### LASER MODULES SERIES 5LT-1

- Semi-telecentric Micro Line
- Gaussian intensity distribution
- Constant line length ca. **4.8 mm**

**LASER MODULES  
SERIES 5LT-2**

- Semi-telecentric Micro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**

This is a printout of the page [https://sukhamburg.com/products/details/5LT-500-1\\_55CM-635-10-H10-A8-CS-7](https://sukhamburg.com/products/details/5LT-500-1_55CM-635-10-H10-A8-CS-7) from 6/4/2023

## CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH  
Kieler Str. 212  
22525 Hamburg  
Germany  
Tel: +49 40 85 39 97-0  
Fax: +49 40 85 39 97-79

[info@sukhamburg.de](mailto:info@sukhamburg.de)  
[www.sukhamburg.com](http://www.sukhamburg.com)

## LEGAL NOTICE

**Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.**

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)