

5LT-75-1+55CM-660-105-M25-A8-P-6

Semi-telecentric Micro Line Generator



FEATURES

Semi-telecentric laser line with constant line length of 4.8 mm.

- Line length: 4.8 mm
- Line width: 27 μm
- Wavelength: 660 nm
- Working distance: 74 mm

-
- Micro Line Generator for small laser line widths and high power density in the focal plane



DESCRIPTION

The laser diode beam source type 5LT-75-1+55CM-660-105-M25-A8-P-6 produces a semi-telecentric laser line with 4.8 mm line length. The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 5 %. The line width is constant along the laser line. Across the laser line the intensity distribution is Gaussian.

The laser has integrated electronics [type P](#) with micro-controller for control of the laser output power. The output power can be controlled using the [modulation input ports \(TTL and analog\)](#), or manually using the potentiometer.

For this laser type the working distance is fixed. A fine-adjustment of the distance between laser and target is recommended for fine-focusing in order to achieve minimal line width.

TECHNICAL DATA

5LT-75-1+55CM-660-105-M25-A8-P-6

Series	5LT	
Order Code	5LT-75-1+55CM-660-105-M25-A8-P-6	
Line profile	Gaussian Intensity Distribution	
Line type	Laser Micro Line	
Wavelength	660 +4/-6 nm	
Laser output power	105 mW	
Laser safety class	3B	
Focussing range	74-74 mm	
Working distance	74 mm	
Line length	4.8 mm	
Line width	0.027 mm	
Rayleigh range	1.69 mm	
Edge intensity	5 %	
Diameter laser module	25/28 mm	
Module length	73.1 mm	
Installation length	177.1 mm	
Cable length	1.5 m	
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 ± 0.2 V	
Max. current consumption	0.25 A	
Working temperature	15 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	9 kOhm	9 kOhm
Max. modulation frequency	0.01 kHz	250 kHz
Modulation delay ON/OFF	3000/3000 µs	0.5/0.2 µs
Rise / Fall time	40000/40000 µs	0.5/0.5 µs

DOWNLOADS

[930412000106.pdf](#)

ACCESSORIES

9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile
PS051003E	Power Supply 5 V

RELATED PRODUCTS

LASER MODULES SERIES 5LTM-1

- Semi-telecentric Macro Line
- Gaussian intensity distribution
- Constant line length ca. **4.8 mm**
- Extended depth of focus

LASER MODULES SERIES LNC-5LTM-1

- Semi-telecentric Macro Line
- Gaussian intensity distribution
- Constant line length ca. **4.8 mm**
- Extended depth of focus
- Low noise

LASER MODULES SERIES 13LT

- Semi-telecentric Micro Line
- Uniform intensity distribution
- Constant line length **15 mm**

LASER MODULES SERIES 5LT-2+25CM

- **Compact** semi-telecentric Micro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**

LASER MODULES SERIES 5LT-1

- Semi-telecentric Micro Line
- Gaussian intensity distribution
- Constant line length ca. **4.8 mm**

LASER MODULES SERIES 5LT-2

- Semi-telecentric Micro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**

This is a printout of the page https://sukhamburg.com/products/details/5LT-75-1_55CM-660-105-M25-A8-P-6 from 4/25/2024

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)