

5LTM-100-11+25CM-640-18-H22-A8-S-6

Semi-telecentric compact Macro Line Generator




FEATURES

Semi-telecentric compact laser line with constant line length of 4.8 mm and extended depth of focus.

- Line length: 4.8 mm
- Line width: 93 μm
- Wavelength: 640 nm
- Working distance: 91 mm
- Depth of focus: 28.5 mm

- Macro Line Generator for extended depth of focus



DESCRIPTION

The laser diode beam source type 5LTM-100-11+25CM-640-18-H22-A8-S-6 produces a semi-telecentric laser line with 4.8 mm line length and extended depth of focus. The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 14 %. The line width is constant along the laser line. Across the laser line the intensity distribution is approx. Gaussian.

The laser has integrated electronics [type S](#) for control of the laser output power. The output power can be controlled using the [modulation input ports \(TTL and analog\)](#), or manually using the potentiometer.

For this laser type the working distance is fixed. A fine-adjustment of the distance between laser and target is recommended for fine-focusing in order to achieve minimal line width.

TECHNICAL DATA

5LTM-100-11+25CM-640-18-H22-A8-S-6

Series	5LTM	
Order Code	5LTM-100-11+25CM-640-18-H22-A8-S-6	
Line profile	Gaussian Intensity Distribution	
Line type	Laser Macro Line	
Wavelength	640 +5/-5 nm	
Laser output power	18 mW	
Laser safety class	3B	
Focussing range	91-91 mm	
Working distance	91 mm	
Line length	4.8 mm	
Line width	0.093 mm	
Depth of focus	28.5 mm	
Edge intensity	14 %	
Diameter laser module	12 mm	
Module length	66.1 mm	
Installation length	187.1 mm	
Cable length	1.5 m	
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 ± 0.25 V	
Max. current consumption	0.25 A	
Working temperature	0 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	22 kOhm	22 kOhm
Max. modulation frequency	50 kHz	1000 kHz
Modulation delay ON/OFF	4/0.5 µs	0.05/0.05 µs
Rise / Fall time	5/4 µs	0.1/0.02 µs

DOWNLOADS



[921120000636.pdf](#)

ACCESSORIES

9D-12 Screwdriver WS 1.2

PS051003E Power Supply 5 V

RELATED PRODUCTS

LASER MODULES SERIES 5LT-2+25CM

- **Compact** semi-telecentric Micro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**

LASER MODULES SERIES LNC-5LTM-2

- Semi-telecentric Macro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**
- Extended depth of focus
- Low noise

LASER MODULES SERIES 13LTM

- Semi-telecentric Macro Line
- Uniform intensity distribution
- Constant line length **15 mm**
- Extended depth of focus

LASER MODULES SERIES 5LTM-1+25CM

- **Compact** semi-telecentric Macro Line
- Gaussian intensity distribution
- Constant line length ca. **4.8 mm**
- Extended depth of focus

LASER MODULES SERIES 5LTM-1

- Semi-telecentric Macro Line
- Gaussian intensity distribution
- Constant line length ca. **4.8 mm**
- Extended depth of focus

LASER MODULES SERIES 5LTM-2

- Semi-telecentric Macro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**
- Extended depth of focus

This is a printout of the page https://sukhamburg.com/products/details/5LTM-100-11_25CM-640-18-H22-A8-S-6 from 6/4/2023

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)