

## 5LTM-330-22+25CM-405-9-Y07-A7.5-B-4

Semi-telecentric compact Macro Line Generator



### FEATURES

Semi-telecentric compact laser line with constant line length of 2.4 mm and extended depth of focus.

- Line length: 2.4 mm
- Line width: 112  $\mu\text{m}$
- Wavelength: 405 nm
- Working distance: 319 mm
- Depth of focus: 49.1 mm

- Macro Line Generator for extended depth of focus



## DESCRIPTION

The laser diode beam source type 5LTM-330-22+25CM-405-9-Y07-A7.5-B-4 produces a semi-telecentric laser line with 2.4 mm line length. In this case the line length is given on the 13.5%-level. The intensity profile is Gaussian in line direction and the line is truncated at 4.8 mm. The line width is constant along the laser line. Across the laser line the intensity distribution is approx. Gaussian.

The laser has integrated electronics [type B](#) for control of the laser output power. The output power can be controlled using the [modulation input port \(TTL\)](#) or manually using the potentiometer.

For this laser type the working distance is fixed. A fine-adjustment of the distance between laser and target is recommended for fine-focusing in order to achieve minimal line width.

**TECHNICAL DATA**

5LTM-330-22+25CM-405-9-Y07-A7.5-B-4

<b>Series</b>	5LTM
<b>Order Code</b>	5LTM-330-22+25CM-405-9-Y07-A7.5-B-4
<b>Line profile</b>	Gaussian Intensity Distribution
<b>Line type</b>	Laser Macro Line
<b>Wavelength</b>	405 +5/-5 nm
<b>Laser output power</b>	9 mW
<b>Laser safety class</b>	3B
<b>Focussing range</b>	319-319 mm
<b>Working distance</b>	319 mm
<b>Line length</b>	2.4 mm
<b>Line width</b>	0.112 mm
<b>Depth of focus</b>	49.1 mm
<b>Edge intensity</b>	9 %
<b>Diameter laser module</b>	12 mm
<b>Module length</b>	66.1 mm
<b>Installation length</b>	415.1 mm
<b>Cable length</b>	1.5 m
<b>Connector type</b>	Lumberg SV40 IEC 61076-2-106
<b>Supply voltage</b>	12 ± 0.5 V
<b>Max. current consumption</b>	0.16 A
<b>Working temperature</b>	0 - 40 °C
<b>Modulation inputs</b>	TTL
<b>Input resistance</b>	110 kOhm
<b>Max. modulation frequency</b>	0.2 kHz
<b>Modulation delay ON/OFF</b>	500/500 µs
<b>Rise / Fall time</b>	10/20 µs

**DOWNLOADS**[921120000636.pdf](#)

## ACCESSORIES

9D-12 Screwdriver WS 1.2

PS120516E Power Supply 12 V

## RELATED PRODUCTS

### LASER MODULES SERIES 5LT-2+25CM

- **Compact** semi-telecentric Micro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**

### LASER MODULES SERIES LNC-5LTM-2

- Semi-telecentric Macro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**
- Extended depth of focus
- Low noise

### LASER MODULES SERIES 13LTM

- Semi-telecentric Macro Line
- Uniform intensity distribution
- Constant line length **15 mm**
- Extended depth of focus

### LASER MODULES SERIES 5LTM-1+25CM

- **Compact** semi-telecentric Macro Line
- Gaussian intensity distribution
- Constant line length ca. **4.8 mm**
- Extended depth of focus

### LASER MODULES SERIES 5LTM-1

- Semi-telecentric Macro Line
- Gaussian intensity distribution
- Constant line length ca. **4.8 mm**
- Extended depth of focus

### LASER MODULES SERIES 5LTM-2

- Semi-telecentric Macro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**
- Extended depth of focus

This is a printout of the page [https://sukhamburg.com/products/details/5LTM-330-22\\_25CM-405-9-Y07-A7\\_5-B-4](https://sukhamburg.com/products/details/5LTM-330-22_25CM-405-9-Y07-A7_5-B-4) from 3/29/2023

## CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

[info@sukhamburg.de](mailto:info@sukhamburg.de)

[www.sukhamburg.com](http://www.sukhamburg.com)

## LEGAL NOTICE

**Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.**

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)