

5LTM-75-11+25CM-785-59-Q06-A8-S-6

Semi-telecentric compact Macro Line Generator




FEATURES

Semi-telecentric compact laser line with constant line length of 4.8 mm and extended depth of focus.

- Line length: 4.8 mm
- Line width: 85 μm
- Wavelength: 785 nm
- Working distance: 68 mm
- Depth of focus: 19.7 mm

- Macro Line Generator for extended depth of focus



DESCRIPTION

The laser diode beam source type 5LTM-75-11+25CM-785-59-Q06-A8-S-6 produces a semi-telecentric laser line with 4.8 mm line length and extended depth of focus. The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 3 %. The line width is constant along the laser line. Across the laser line the intensity distribution is approx. Gaussian.

The laser has integrated electronics [type S](#) for control of the laser output power. The output power can be controlled using the [modulation input ports \(TTL and analog\)](#), or manually using the potentiometer.

For this laser type the working distance is fixed. A fine-adjustment of the distance between laser and target is recommended for fine-focusing in order to achieve minimal line width.

TECHNICAL DATA

5LTM-75-11+25CM-785-59-Q06-A8-S-6

Series	5LTM	
Order Code	5LTM-75-11+25CM-785-59-Q06-A8-S-6	
Line profile	Gaussian Intensity Distribution	
Line type	Laser Macro Line	
Wavelength	785 +10/-10 nm	
Laser output power	59 mW	
Laser safety class	3B	
Focussing range	68-68 mm	
Working distance	68 mm	
Line length	4.8 mm	
Line width	0.085 mm	
Depth of focus	19.7 mm	
Edge intensity	3 %	
Diameter laser module	12 mm	
Module length	66.1 mm	
Installation length	164.1 mm	
Cable length	1.5 m	
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 ± 0.25 V	
Max. current consumption	0.25 A	
Working temperature	0 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	22 kOhm	22 kOhm
Max. modulation frequency	50 kHz	1000 kHz
Modulation delay ON/OFF	4/0.5 µs	0.05/0.05 µs
Rise / Fall time	5/4 µs	0.1/0.02 µs

DOWNLOADS

[921120000636.pdf](#)

ACCESSORIES

9D-12 Screwdriver WS 1.2

PS051003E Power Supply 5 V

RELATED PRODUCTS

LASER MODULES SERIES 5LT-2+25CM

- **Compact** semi-telecentric Micro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**

LASER MODULES SERIES LNC-5LTM-2

- Semi-telecentric Macro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**
- Extended depth of focus
- Low noise

LASER MODULES SERIES 13LTM

- Semi-telecentric Macro Line
- Uniform intensity distribution
- Constant line length **15 mm**
- Extended depth of focus

LASER MODULES SERIES 5LTM-1+25CM

- **Compact** semi-telecentric Macro Line
- Gaussian intensity distribution
- Constant line length ca. **4.8 mm**
- Extended depth of focus

LASER MODULES SERIES 5LTM-1

- Semi-telecentric Macro Line
- Gaussian intensity distribution
- Constant line length ca. **4.8 mm**
- Extended depth of focus

LASER MODULES SERIES 5LTM-2

- Semi-telecentric Macro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**
- Extended depth of focus

This is a printout of the page https://sukhamburg.com/products/details/5LTM-75-11_25CM-785-59-Q06-A8-S-6 from 4/19/2024

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)