

5M-S325+25CM-639-18-H18-A8-S-6

Compact Laser Micro Focus Generator with elliptical Gaussian beam profile



FEATURES

Compact Laser spot with elliptical Gaussian beam profile.

Spot diameter: 0.055 x 0.14 mm

Wavelength: 639 nmWorking distance: 317 mm

 Micro Focus Generator for small spot widths and high power density in the focal plane



DESCRIPTION

The laser diode beam source type 5M-S325+25CM-639-18-H18-A8-S-6 produces an elliptical laser spot with elliptical Gaussian intensity distribution.

The laser has integrated electronics $\underline{type\ S}$ for control of the laser output power. The output power can be controlled using the $\underline{modulation\ input\ ports\ (TTL\ and\ analog)}$ or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that the spot diameter increases proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

5M-S325+25CM-639-18-H18-A8-S-6

Series 5M



Line profile Wavelength Laser output power Laser safety class Focussing range Working distance Spot height Spot width	Gaussian Inte	18 mW 38 260-430 mm 317 mm 0.055 mm
Laser output power Laser safety class Focussing range Working distance Spot height		18 mW 3B 260-430 mm 317 mm 0.14 mm
Laser safety class Focussing range Working distance Spot height		3B 260-430 mm 317 mm 0.14 mm
Focussing range Working distance Spot height		260-430 mm 317 mm 0.14 mm
Working distance Spot height		317 mm 0.14 mm
Spot height		0.14 mm
· · · · · · · · · · · · · · · · · · ·		
Spot width		0.055 mm
Rayleigh range	7.46 mm	
Diameter laser module	12 mm	
Module length	60.7 mm	
Installation length	407.7 mm	
Cable length		1.5 m
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage		5 ± 0.25 V
Max. current consumption		0.25 A
Working temperature		0 - 40 °C
Modulation inputs	Analog	TTL
Input resistance	22 kOhm	22 kOhm
Max. modulation frequency	50 kHz	1000 kHz
Modulation delay ON/OFF	4/0.5 μs	0.05/0.05 μs
Rise / Fall time	5/4 μs	0.1/0.02 μs

ACCESSORIES

60EX-4 Eccentric key with a stroke of \pm 0.5 mm.

60EX-4-L Alternative eccentric key with long handle with a

stroke of \pm 0.5 mm.

9D-12 Screwdriver WS 1.2

PS051003E Power Supply 5 V

RELATED PRODUCTS



LASER MODULES

Compact Laser Macro Focus Generator

SERIES 5MM

Circular beam profile andExtended depth of focus

LASER MODULES

Micro Focus Generator

SERIES 13MC

Rotationally symmetric, Gaussian beam profile

LASER MODULES

Compact Laser Micro Focus Generator

SERIES 5MC

Rotationally symmetric, Gaussian beam profile

LASER MODULES

Micro Focus Generator

SERIES 13M

Elliptical Gaussian beam profile

This is a printout of the page $\underline{\text{https://sukhamburg.com/products/details/5M-S325}}$ 25CM-639-18-H18-A8-S-6 from 5/4/2024

CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany

Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]