

## 5M-S325+55CM-660-105-M25-A8-PS-7

Compact Laser Micro Focus Generator with elliptical Gaussian beam profile



#### **FEATURES**

Compact Laser spot with elliptical Gaussian beam profile.

Spot diameter: 0.068 x 0.116 mm

Wavelength: 660 nm

Working distance: 317 mm

- Micro Focus Generator for small spot widths and high power density in the focal plane
- With RS232 interface





### DESCRIPTION

The laser diode beam source type 5M-S325+55CM-660-105-M25-A8-PS-7 produces an elliptical laser spot with elliptical Gaussian intensity distribution.

The laser has integrated electronics <u>type PS</u> with micro-controller for control of the laser output power and serial interface (RS232). The output power can be controlled using the <u>modulation input ports (TTL and analog)</u> or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that the spot diameter increases proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

### **TECHNICAL DATA**

5M-S325+55CM-660-105-M25-A8-PS-7



Line profile  Wavelength  Laser output power  Laser safety class  Focussing range  Working distance  Spot height  Spot width	660-105	: MOE AO DO Z		
Wavelength  Laser output power  Laser safety class  Focussing range  Working distance  Spot height  Spot width		5M-S325+55CM-660-105-M25-A8-PS-7		
Laser output power  Laser safety class  Focussing range  Working distance  Spot height  Spot width	Gaussian Intensity Distribution			
Laser safety class  Focussing range  Working distance  Spot height  Spot width	660 +4/-6 nm			
Focussing range Working distance Spot height Spot width	105 mW			
Working distance Spot height Spot width	3B			
Spot height Spot width	260-430 mm			
Spot width	317 mm			
·	0.116 mm			
Payloigh range	0.068 mm			
Rayleigh range	11.2 mm			
Diameter laser module	25/28 mm			
Module length	73.1 mm			
Installation length	420.1 mm			
Cable length	1.5 m			
Connector type Lumberg S	Lumberg SV70 IEC 61076-2-106			
Supply voltage	5 ± 0.2 V			
Max. current consumption		0.25 A		
Working temperature		15 - 40 °C		
Modulation inputs Ar	nalog	TTL		
Input resistance 9 k	Ohm	9 kOhm		
Max. modulation frequency 0.001	L kHz	250 kHz		
Modulation delay ON/OFF 3000/300	00 μs	0.5/0.2 μs		
Rise / Fall time 200000/20000	00 μs	0.8/0.4 μs		
Interface		RS232		

# **ACCESSORIES**

**60EX-4** Eccentric key with a stroke of  $\pm$  0.5 mm.

**60EX-4-L** Alternative eccentric key with long handle with a

stroke of ± 0.5 mm.

**9D-12** Screwdriver WS 1.2

# **RELATED PRODUCTS**



**LASER MODULES** 

Compact Laser Macro Focus Generator

**SERIES 5MM** 

Circular beam profile andExtended depth of focus

LASER MODULES

Micro Focus Generator

**SERIES 13MC** 

Rotationally symmetric, Gaussian beam profile

LASER MODULES

Compact Laser Micro Focus Generator

**SERIES 5MC** 

• Rotationally symmetric, Gaussian beam profile

**LASER MODULES** 

Micro Focus Generator

**SERIES 13M** 

Elliptical Gaussian beam profile

This is a printout of the page  $\underline{\text{https://sukhamburg.com/products/details/5M-S325}}$  55CM-660-105-M25-A8-PS-7 from 4/25/2024

### **CONTACT**

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212 22525 Hamburg Germany

Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

### LEGAL NOTICE

### Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]