5M-S325+55CM-785-90-Q06-A8-CS-7

Compact Laser Micro Focus Generator with elliptical Gaussian beam profile

FEATURES

Compact Laser spot with elliptical Gaussian beam profile.

- Spot diameter: 0.086 x 0.153 mm
- Wavelength: 785 nm
- Working distance: 317 mm

- Micro Focus Generator for small spot widths and high power density in the focal plane
- With RS232 interface

DESCRIPTION

The laser diode beam source type 5M-S325+55CM-785-90-Q06-A8-CS-7 produces an elliptical laser spot with elliptical Gaussian intensity distribution.

The laser has integrated electronics type CS for control of the laser output power and serial interface (RS232). The output power can be controlled using the modulation input ports (TTL and analog) or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that the spot diameter increases proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

5M-S325+55CM-785-90-Q06-A8-CS-7

Series		5M
Order Code		5M-S325+55CM-785-90-Q06-A8-CS-7
Line profile		Gaussian Intensity Distribution
Wavelength		785 +10/-10 nm
Laser output power		90 mW
Laser safety class		3B
Focussing range		260-430 mm
Working distance		317 mm
Spot height		0.153 mm
Spot width		0.086 mm
Rayleigh range		14.9 mm
Diameter laser module		25/28 mm
Module length		73.1 mm
Installation length		420.1 mm
Cable length		1.5 m
Connector type		Lumberg SV70 IEC 61076-2-106
Supply voltage		5 ± 0.2 V
Max. current consumption		0.25 A
Working temperature		0 - 40 °C
Modulation inputs	Analog	TTL
Input resistance	9 kOhm	9 kOhm
Max. modulation frequency	0.001 kHz	250 kHz
Modulation delay ON/OFF	3000/3000 µs	0.5/0.2 µs
Rise / Fall time	200000/200000 µs	0.8/0.4 µs
Interface		RS232

ACCESSORIES

60EX-4	Eccentric key with a stroke of ± 0.5 mm.
60EX-4-L	Alternative eccentric key with long handle with a stroke of ± 0.5 mm.
9D-12	Screwdriver WS 1.2

RELATED PRODUCTS

LASER MODULES SERIES 5MM	▪ **Compact** Laser Macro Focus Generator ▪ **Circular** beam profile and ▪ Extended depth of focus
LASER MODULES SERIES 13MC	▪ Micro Focus Generator ▪ **Rotationally symmetric**, Gaussian beam profile
LASER MODULES SERIES 5MC	▪ **Compact** Laser Micro Focus Generator ▪ **Rotationally symmetric**, Gaussian beam profile
LASER MODULES SERIES 13M	▪ Micro Focus Generator ▪ Elliptical Gaussian beam profile

This is a printout of the page https://sukhamburg.com/products/details/5M-S325_55CM-785-90-Q06-A8-CS-7 from 4/20/2024

CONTACT

For more information please contact:
Schäfter + Kirchhoff GmbH
Kieler Str. 212
22525 Hamburg
Germany
Tel: +49 40 85 39 97-0
Fax: +49 40 85 39 97-79

info@sukhamburg.de
www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]