

5M-S50+25CM-635-10-H10-A8-S-6

Compact Laser Micro Focus Generator with elliptical Gaussian beam profile



FEATURES

Compact Laser spot with elliptical Gaussian beam profile.

Spot diameter: 0.008 x 0.021 mm

Wavelength: 635 nmWorking distance: 46 mm

 Micro Focus Generator for small spot widths and high power density in the focal plane



DESCRIPTION

The laser diode beam source type 5M-S50+25CM-635-10-H10-A8-S-6 produces an elliptical laser spot with elliptical Gaussian intensity distribution.

The laser has integrated electronics $\underline{type\ S}$ for control of the laser output power. The output power can be controlled using the $\underline{modulation\ input\ ports\ (TTL\ and\ analog)}$ or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that the spot diameter increases proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

5M-S50+25CM-635-10-H10-A8-S-6

Series 5M



Laser output power Laser safety class Focussing range Working distance Spot height Spot width Rayleigh range Diameter laser module Module length Installation length Cable length	110-A8-S-6	
Laser safety class Focussing range Working distance Spot height Spot width Rayleigh range Diameter laser module Module length Installation length Cable length Connector type Supply voltage Max. current consumption Working temperature	Distribution	
Laser safety class Focussing range Working distance Spot height Spot width Rayleigh range Diameter laser module Module length Installation length Cable length Connector type Lumberg SV50 IEC 63 Supply voltage Max. current consumption Working temperature	ngth 635 +10/-10 nm	
Focussing range Working distance Spot height Spot width Rayleigh range Diameter laser module Module length Installation length Cable length Connector type Lumberg SV50 IEC 63 Supply voltage Max. current consumption Working temperature	10 mW	
Working distance Spot height Spot width Rayleigh range Diameter laser module Module length Installation length Cable length Connector type Lumberg SV50 IEC 62 Supply voltage Max. current consumption Working temperature	3B	
Spot height Spot width Rayleigh range Diameter laser module Module length Installation length Cable length Connector type Lumberg SV50 IEC 63 Supply voltage Max. current consumption Working temperature	35-70 mm	
Spot width Rayleigh range Diameter laser module Module length Installation length Cable length Connector type Lumberg SV50 IEC 63 Supply voltage Max. current consumption Working temperature	46 mm	
Rayleigh range Diameter laser module Module length Installation length Cable length Connector type Lumberg SV50 IEC 62 Supply voltage Max. current consumption Working temperature	0.021 mm	
Diameter laser module Module length Installation length Cable length Connector type Lumberg SV50 IEC 62 Supply voltage Max. current consumption Working temperature	0.008 mm	
Module length Installation length Cable length Connector type Lumberg SV50 IEC 62 Supply voltage Max. current consumption Working temperature	leigh range 0.175 mm	
Installation length Cable length Connector type Lumberg SV50 IEC 62 Supply voltage Max. current consumption Working temperature	12 mm	
Cable length Connector type Lumberg SV50 IEC 63 Supply voltage Max. current consumption Working temperature	60.7 mm	
Connector type Lumberg SV50 IEC 63 Supply voltage Max. current consumption Working temperature	136.7 mm	
Supply voltage Max. current consumption Working temperature	1.5 m	
Max. current consumption Working temperature	Lumberg SV50 IEC 61076-2-106	
Working temperature	5 ± 0.25 V	
<u> </u>	0.25 A	
Modulation inputs Analog	0 - 40 °C	
:	TTL	
Input resistance 22 kOhm	22 kOhm	
Max. modulation frequency 50 kHz	1000 kHz	
Modulation delay ON/OFF4/0.5 μs0	.05/0.05 μs	
Rise / Fall time 5/4 µs	0.1/0.02 μs	

ACCESSORIES

60EX-4 Eccentric key with a stroke of \pm 0.5 mm.

60EX-4-L Alternative eccentric key with long handle with a

stroke of \pm 0.5 mm.

9D-12 Screwdriver WS 1.2

PS051003E Power Supply 5 V

RELATED PRODUCTS



LASER MODULES

Compact Laser Macro Focus Generator

SERIES 5MM

Circular beam profile andExtended depth of focus

·

LASER MODULES

Micro Focus Generator

SERIES 13MC

Rotationally symmetric, Gaussian beam profile

LASER MODULES

Compact Laser Micro Focus Generator

SERIES 5MC

Rotationally symmetric, Gaussian beam profile

LASER MODULES

Micro Focus Generator

SERIES 13M

Elliptical Gaussian beam profile

This is a printout of the page https://sukhamburg.com/products/details/5M-S50 25CM-635-10-H10-A8-S-6 from 5/3/2024

CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany

Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]